



# CONSTRUCTION EQUIPMENT

SWA474120-1 SENNEBOGEN 835 835.0.2487 - FRONT LEFT FINAL DRIVE



**Sample No:** VCP431478  
**Oil Type:** VOLVO PREMIUM GEAR OIL 80W-90 GL-5  
**Job No:** SWA474120-1



## SAMPLE INFORMATION

Sample Number	<b>VCP431478</b>	VCP415318	---	---
Sample Date	<b>05 Feb 2024</b>	09 Oct 2023	---	---
Machine Hours	<b>11725</b>	11163	---	---
Oil Hours	<b>500</b>	2000	---	---
Oil Changed	<b>Not Chngd</b>	Changed	---	---
Sample Status	<b>NORMAL</b>	ABNORMAL	---	---

### ALTA EQUIPMENT COMPANY

1035 WYLIE DRIVE  
 BLOOMINGTON, IL  
 US 61705

Contact: JUSTIN PERRY  
 justin.perry@altg.com  
 T: (309)533-9285  
 F:



## OIL CONDITION

Visc @ 40°C	cSt	<b>143</b>	144	---	---
-------------	-----	------------	-----	-----	-----



## CONTAMINATION

Water	%	<b>NEG</b>	NEG	---	---
Silicon	ppm	<b>3</b>	4	---	---
Sodium	ppm	<b>0</b>	<1	---	---
Potassium	ppm	<b>1</b>	0	---	---

### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.



## WEAR METALS

Iron	ppm	<b>55</b>	49	---	---
Copper	ppm	<b>6</b>	5	---	---
Lead	ppm	<b>0</b>	0	---	---
Tin	ppm	<b>0</b>	0	---	---
Aluminum	ppm	<b>2</b>	0	---	---
Chromium	ppm	<b>&lt;1</b>	0	---	---
Molybdenum	ppm	<b>0</b>	0	---	---
Nickel	ppm	<b>0</b>	0	---	---
Titanium	ppm	<b>0</b>	0	---	---
Silver	ppm	<b>0</b>	0	---	---
Manganese	ppm	<b>&lt;1</b>	<1	---	---
Vanadium	ppm	<b>0</b>	0	---	---



## ADDITIVES

Calcium	ppm	<b>28</b>	38	---	---
Magnesium	ppm	<b>17</b>	27	---	---
Zinc	ppm	<b>32</b>	40	---	---
Phosphorus	ppm	<b>1649</b>	1828	---	---
Barium	ppm	<b>&lt;1</b>	2	---	---
Boron	ppm	<b>177</b>	137	---	---

**Depot:** VOLVO5054  
**Unique No:** 10888738  
**Signed:** Wes Davis  
**Report Date:** 22 Feb 2024



# CONSTRUCTION EQUIPMENT



## VOLVO GRAPHS

