

## **CONSTRUCTION EQUIPMENT**

SVC53073 MORRUNE EXC VOLVO EC160BLC 11381 - FRONT RIGHT FINAL DRIV

Sample No: VCP407153

Oil Type: GEAR OIL SAE 80W90

**Job No:** SVC53073 MORRUNE EXC

SAMPLE	INFORMATION			
Sample Number	_	VCP407153	 	
Sample Date		28 Feb 2024	 	
Machine Hours		6886	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		SEVERE	 	
Sumple Status		SEVERE		
VOLVO				
OIL COND	ITION			
Visc @ 40°C	cSt	<b>148</b>	 	
VOLVO				
CONTAM	INATION			
_				
Water	%	NEG	 	
Silicon	ppm	<b>1053</b>	 	
Sodium	ppm	■ 57	 	
Potassium	ppm	■84	 	
VOLVO				
WEAR M	FTAIS			
Iron		<b>2674</b>	 	
Copper	ppm	<b>2074</b>		
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>■</b> <1	 	
	ppm	_	 	
Aluminum	ppm	<b>○</b> 206 <b>△</b> 22	 	
	ppm		 	
Molybdenum	ppm	<b>0</b>		
Nickel	ppm	<b>3</b>	 	
Titanium	ppm	<b>11</b>	 	
Silver	ppm	0	 	
Manganese	ppm	<b>1</b> 4	 	
Vanadium	ppm	<1	 	
VOLVO				
<b>ADDITIV</b>	23			
Calcium	ppm	<b>□38</b>	 	
Magnesium	ppm	<b>■</b> 19	 	
Zinc	ppm	<b>■11</b>	 	
Phosphorus	ppm	<b>1991</b>	 	
Barium	ppm	<b>1</b> 1001	 	
Boron	ppm	<b>152</b>	 	
DOTOTI	PPIII	1J£		



### **TYLER EQUIPMENT CORPORATION**

1980 BERLIN TURNPIKE BERLIN, CT US 06037 Contact: KYLE SCHMITZ kschmitz@tylerequipment.com

T: (860)356-0840 F: (860)828-6727

### Diagnosis

We advise that you check all areas where dirt can enter the system. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The oil is no longer serviceable due to the presence of contaminants.

Depot:VOLVO0005Unique No:10909943Signed:Jonathan HesterReport Date:05 Mar 2024



# **CONSTRUCTION EQUIPMENT**





