

## CONSTRUCTION EQUIPMENT FUCHS MHL340F2 340410/5529 - REAR RIGHT FINAL DRIVE



Sample No: VCP443520

**Oil Type:** GEAR OIL SAE 80W90

Job No:

SAMPLE	INFORMATIO	N		
Sample Number	<u>.</u>	VCP443520	 	
Sample Date		18 Mar 2024	 	
Machine Hours		6030	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
VOLVO	DITION			
OIL CON				
Visc @ 40°C	cSt	<b>133</b>	 	
CONTAN	MINATION			
Water	%	NEG	 	
Silicon		NEG ■ 17		
Sodium	ppm	<b>■</b> 3	 	
Potassium	ppm	<b>2</b>	 	
Potassium	ppm	<u> </u>	 	
VOLVO				
WEAR N	METALS			
Iron	ppm	<b>260</b>	 	
Copper	ppm	■36	 	
Lead	ppm	<b>2</b>	 	
Tin	ppm	<b>■&lt;1</b>	 	
Aluminum	ppm	<b>2</b>	 	
Chromium	ppm	<b>2</b>	 	
Molybdenum	ppm	<b>10</b>	 	
Nickel	ppm	<b>2</b>	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	<b>6</b>	 	
Vanadium	ppm	<1	 	
	•			
ADDITIV	IFS			
		= 204		
Calcium	ppm	<b>304</b>	 	
Magnesium	ppm	<b>17</b>	 	
Zinc	ppm	<b>■</b> 168	 	
Phosphorus	ppm	■388	 	
Barium	ppm	<b>-</b> <1	 	
Boron	ppm	<b>10</b>	 	



ALTA EQUIPMENT CO - ORLAND PARK 5000 INDUSTRIAL HWY GARY, IN US 46406 Contact: DAVE ENG DAVE.ENG@ALTG.COM T: (312)350-2560 F:

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO8885Unique No:10938175Signed:Don BaldridgeReport Date:22 Mar 2024



## **CONSTRUCTION EQUIPMENT**





