

CONSTRUCTION EQUIPMENT VULCAN VOLVO A40G 352031 - FRONT AXLE



Sample No: VCP384556

Oil Type: GEAR OIL SAE 80W90

Job No: VULCAN

VOLVO	INFORMATION			
	INFURMATION			
Sample Number		VCP384556	 	
Sample Date		02 Apr 2024	 	
Machine Hours		6766	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	145	 	
VOLVO	UNIA TION			
LUNTAM	IINATION			
Water	%	NEG	 	
Silicon	ppm	2	 	
Sodium	ppm	1	 	
Potassium	ppm	2	 	
WEAR M	IFTAL C			
_				
Iron	ppm	53	 	
Copper	ppm	■<1	 	
Lead	ppm	■0	 	
Tin	ppm	■<1	 	
Aluminum	ppm	1	 	
Chromium	ppm	1	 	
Molybdenum	ppm	1	 	
Nickel	ppm	■<1	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	2	 	
Vanadium	ppm	0	 	
VOLVO			 	
ADDITIV	ES			
Calcium	ppm	28	 	
Magnesium	ppm	1	 	
Zinc	ppm	11	 	
Phosphorus	ppm	1049	 	
Barium	ppm	■0	 	
Boron	ppm	201	 	
שטוטוו	ppiii	<u> </u>	 	



SCOTT EQUIPMENT COMPANY LLC - Lavergne
1231 BRIDGESTONE PARKWAY
LAVERGNE, TN
US 37086
Contact: CLAY COULTER
CCOULTER@SCOTTCOMPANIES.COM
T: (615)793-3888
F: (615)793-9655

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0129Unique No:10963685Signed:Wes DavisReport Date:05 Apr 2024

Contact/Location: CLAY COULTER - VOLVO0129



CONSTRUCTION EQUIPMENT





