

CONSTRUCTION EQUIPMENT 41614 D AND L SITE VOLVO A30G 753380 - FRONT AXLE



Sample No: VCP447074

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: 41614 D AND L SITE

VOLVO	INFORMATIO	V		
	E INFORMATIO			
Sample Number		VCP447074	VCP416530	
Sample Date		02 Apr 2024	15 Nov 2023	
Machine Hours		1083	622	
Oil Hours		0	600	
Oil Changed		Changed	Changed	
Sample Status		ATTENTION	NORMAL	
OIL CON	DITION			
Visc @ 40°C	cSt	58.7	94.1	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	■3	6	
Sodium	ppm	1	□0	
Potassium	ppm	_ 0	1 6	
	1.1.			
VOLVO	AETAL C			
WEAR N	NE I ALS			
Iron	ppm	94	1 92	
Copper	ppm	10	2 0	
Lead	ppm	0	0	
Tin	ppm	0	- <1	
Aluminum	ppm	0	1	
Chromium	ppm	1	5	
Molybdenum	ppm	1	6	
Nickel	ppm	■ 0	3	
Titanium	ppm	0	<1	
Silver	ppm	0	0	
Manganese	ppm	4	1 1	
Vanadium	ppm	0	0	
ADDITIV	VES			
Calcium	ppm	157	472	
Magnesium	ppm	■0	2	
Zinc	ppm	■ 59	■201	
Phosphorus	ppm	2154	1309	
Barium	ppm	0	■0	
Boron	ppm	272	311	



215 - ASCENDUM MACHINERY INC - CAYCE 2303 AIRPORT BLVD CAYCE, SC US 29033 Contact: ROBBY HERLONG robby.herlong@ascendummachinery.com T: (803)394-6783 F: (803)791-9920

Diagnosis

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Confirm oil type.

Depot:VOLVO0013Unique No:10966527Signed:Don BaldridgeReport Date:10 Apr 2024



CONSTRUCTION EQUIPMENT





