CONSTRUCTION EQUIPMENT SW-31591-2 RAMSEY VOLVO A60H 350374 - FRONT AXLE

Sample No: VCP443089

VOLVO

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: SW-31591-2 RAMSEY

					_
	E INFORMATION				
Sample Number	-	VCP443089		 	-
Sample Date		01 Apr 2024		 	ARNOLD MACHINERY COMPANY
Machine Hours		522		 	2975 WEST 2100 SOUTH
Oil Hours		522		 	SALT LAKE CITY, UT
Oil Changed		Changed		 	US 84119
Sample Status		ATTENTION		 	Contact: KEVIN ARNONE
					karnone@arnoldmachinery.com
OIL CON					T: (801)972-4000
			<u> </u>		F: (801)975-9434
Visc @ 40°C	cSt	6 51.5		 	
VOLVO					Diagnosis
CONTAN	MINATION				The oil change at the time of
Water	%	NEG		 	sampling has been noted. Resample
Silicon	ppm	3		 	at the next service interval to
Sodium	ppm	1		 	monitor.All component wear rates
Potassium	ppm	0		 	are normal. There is no indication of
					any contamination in the oil. The oil
WEAR N	AFTAIS				viscosity is lower than normal. Confirm oil type.
-		=146			common type.
Iron	ppm	146		 	
Copper	ppm	∎1		 	
Lead Tin	ppm	0		 	
Aluminum	ppm	0		 	
Chromium	ppm ppm	2		 	
Molybdenum	ppm	3		 	
Nickel	ppm	0		 	
Titanium	ppm	0		 	
Silver	ppm	0		 	
Manganese	ppm	5		 	
Vanadium	ppm	0		 	
	ppiii				
VOLVO	155				
	VES	<u>.</u>	<u> </u>	 <u>.</u>	
Calcium	ppm	334		 	
Magnesium	ppm	1		 	
Zinc	ppm	149		 	
Phosphorus	ppm	2318		 	
Barium	ppm	0		 	
Boron	ppm	267		 	

CONSTRUCTION EQUIPMENT



GRAPHS

VOLVO

