

CONSTRUCTION EQUIPMENT VOLVO A45G 353418 - REAR AXLE



Sample No: VCP436865

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No:

CVMDIE	INFORMATIO			
_	. INFURMATIO			_
Sample Number		VCP436865	VCP416381	
Sample Date		05 Apr 2024	20 Oct 2023	
Machine Hours		1960	997	
Oil Hours		0	0	
Oil Changed		Not Changd	Changed	
Sample Status		ATTENTION	ABNORMAL	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	57.3	52.7	
			<u> </u>	
VOLVO	AINATION			
LUNIAN	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	■7	3	
Sodium	ppm	■ 4	1	
Potassium	ppm	■ 4	3	
WEAR N	AFTAI S			
Iron		202	111	
Copper	ppm	202	111	
Lead	ppm	0	0	
Tin		0	0	
Aluminum	ppm	2	0	
Chromium	ppm	3	<1	
Molybdenum	ppm	7	3	
Nickel	ppm	■ <1	0	
Titanium	ppm	<1	0	
Silver	ppm	0	0	
Manganese	ppm	™ 6	4	
Vanadium	ppm	<1	0	
variacium	ppill	\ 1	U	
VOLVO				
ADDITIN	lez			
Calcium	ppm	115	162	
Magnesium	ppm	6	- <1	
Zinc	ppm	50	6 3	
Phosphorus	ppm	2269	2056	
Barium	ppm	0	0	
Boron	ppm	269	296	



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

T:

F: (239)481-3302

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Additive levels indicate the addition of a different brand, or type of oil. Confirm oil type.

Depot:VOLVO0090Unique No:10966545Signed:Don BaldridgeReport Date:10 Apr 2024



CONSTRUCTION EQUIPMENT





