

CONSTRUCTION EQUIPMENT 41614 D AND L SITE VOLVO A 30G 753380 - REAR AXLE



Sample No: VCP447066

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: 41614 D AND L SITE

SAMPLE	INFORMATIO	N		
Sample Number	_	VCP447066	VCP435065	
Sample Date		02 Apr 2024	15 Nov 2023	
Machine Hours		1083	622	
Oil Hours		0	500	
Oil Changed		Changed	Changed	
Sample Status		ATTENTION	NORMAL	
VOLVO	DITION			
OIL CON				
Visc @ 40°C	cSt	58.9	■87.6	
VOLVO				
CONTAN	IINATION			
Water	%	NEG	NEG	
Silicon		MEG ■ 6	1 6	
Sodium	ppm	■ <1	1 0	
Potassium	ppm	3	7	
FOLASSIUIII	ppm		/	
VOLVO				
WEAR M	IETALS			
Iron	ppm	114	■180	
Copper	ppm	■ 9	1 6	
Lead	ppm	0	0	
Tin	ppm	■<1	- <1	
Aluminum	ppm	2	1	
Chromium	ppm	■ 3	4	
Molybdenum	ppm	■ 3	■8	
Nickel	ppm	1	2	
Titanium	ppm	<1	<1	
Silver	ppm	0	0	
Manganese	ppm	4	■10	
Vanadium	ppm	<1	0	
ADDITIV	ES			
Calcium	ppm	246	848	
Magnesium	ppm	<u></u> 2	3	
Zinc	ppm	101	361	
Phosphorus	ppm	2198	1325	
Barium	ppm		- <1	
Boron	ppm	■318	307	



215 - ASCENDUM MACHINERY INC - CAYCE 2303 AIRPORT BLVD CAYCE, SC US 29033 Contact: ROBBY HERLONG robby.herlong@ascendummachinery.com T: (803)394-6783

Diagnosis

F: (803)791-9920

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Confirm oil type.

Depot:VOLVO0013Unique No:10966547Signed:Don BaldridgeReport Date:10 Apr 2024



CONSTRUCTION EQUIPMENT





