Sample No: VCP442639

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No: 5331DR KINSLEY

SAMPLE II	NFORMATION			
Sample Number		VCP442639	 	
Sample Date		05 Apr 2024	 	
Machine Hours		936	 	
Oil Hours		936	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
VOLVO	TION			
OIL CONDI	TIUN			
Visc @ 40°C	cSt	43.8	 	
Acid Number (AN)	mg KOH/g	■ 0.41	 	
CONTAMIN	NATION			
_	_	NEC		
Water	%	NEG	 	
Particles >4µm		57129	 	
Particles >6µm		▲ 15234	 	
Particles > 14µm		<u>^</u> 1034	 	
SO 4406:1999 (c)		23/21/17	 	
Silicon	ppm	4	 	
Sodium	ppm	■ <1	 	
Potassium	ppm	■0	 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	1 <1	 	
Copper	ppm		 	
Lead	ppm	■0	 	
Tin	ppm	■<1	 	
Aluminum	ppm	■ 0	 	
Chromium	ppm	■ 0	 	
Molybdenum	ppm	■0	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	■ 0	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIVE	7			
Calcium	ppm	■ 59	 	
Magnesium	ppm	■0	 	
Zinc	ppm	■393	 	



HIGHWAY EQUIPMENT & SUPPLY CO

PO BOX 127 DRUMS, PA US 18222 Contact: JUSTIN BLOSS justin@hwyequip.com T: (570)788-1127 F: (570)708-2933

Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0022Unique No:10968977Signed:Wes DavisReport Date:11 Apr 2024

ppm

ppm

ppm

■311

0

0

Phosphorus

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

