Sample No: VCP437062

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

**Job No:** 687011

VOLVO	INFORMATION	<b>\</b>		
	INFURMATIUM			
Sample Number		VCP437062	 	
Sample Date		07 Mar 2024	 	
Machine Hours		554	 	
Oil Hours		554	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
OIL CON	NITION			
Visc @ 40°C		<b>175</b>		
	cSt	■175	 	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	 	
Silicon	ppm	<b>16</b>	 	
Sodium	ppm	<b>2</b>	 	
Potassium	ppm	<1	 	
	ρρ			
VOLVO				
WEAR N	METALS			
Iron	ppm	<b>406</b>	 	
Copper	ppm	<b>■</b> <1	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>■</b> 0	 	
Aluminum	ppm	<b>1</b>	 	
Chromium	ppm	<b>■7</b>	 	
Molybdenum	ppm	<b>■&lt;1</b>	 	
Nickel	ppm	<b>■&lt;1</b>	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	<b>10</b>	 	
Vanadium	ppm	<1	 	
ADDITIV	)EC			
_				
Calcium	ppm	■36	 	
Magnesium	ppm	<b>1</b>	 	
Zinc	ppm	<b>41</b>	 	
Phosphorus	ppm	■372	 	
Barium	ppm	<b></b>	 	
_				



## RIPA AND ASSOCIATES 10149 FISHER AVENUE TAMPA, FL US 33619 Contact: ROBERT TURNER rturner@ripatampa.com T:

## Diagnosis

F:

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:RIPTAMUnique No:10976315Signed:Don BaldridgeReport Date:15 Apr 2024

■0

ppm

Boron



## **CONSTRUCTION EQUIPMENT**





