

Sample No: VCP446404

Oil Type: MOBIL MOBILUBE HD 80W90

Job No: A12512 GEN ASPHALT

SAMPLE	INFORMATIO	N		
Sample Number	•	VCP446404	VCP284680	
Sample Date		21 Apr 2024	05 Oct 2020	
Machine Hours		2515	730	
Oil Hours		1000	730	
Oil Changed		Changed	Changed	
Sample Status		NORMAL	NORMAL	
VOLVO	DITION			
OIL CON				
Visc @ 40°C	cSt	■315	169	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	NEG	
Silicon		MEG ■5	11	
Sodium	ppm	■ 0	0	
Potassium	ppm	■ 0	<1	
FOLASSIUIII	ррпп			
VOLVO				
WEAR N	METALS			
Iron	ppm	29	9 5	
Copper	ppm	4	4	
Lead	ppm	-<1	- <1	
Tin	ppm	-<1	<1	
Aluminum	ppm	2	0	
Chromium	ppm		2	
Molybdenum	ppm	-<1	< 1	
Nickel	ppm		0	
Titanium	ppm	<1	<1	
Silver	ppm	0	<1	
Manganese	ppm	■<1	2	
Vanadium	ppm	<1	0	
ADDITIV	VES			
Calcium	ppm	■ 31	6	
Magnesium	ppm	4	1	
Zinc	ppm	■17	3	
Phosphorus	ppm	■ 964	447	
Barium	ppm	2	2	
Boron	ppm	■ 199	5	
DOTOTI	ppiii	1 1 3 3	J J	



HOFFMAN EQUIPMENT - LIONVILLE

120 GORDON DRIVE LIONVILLE, PA US 19341 Contact: JIM FEHR jim.fehr@hoffmanequip.com T: (610)363-9200 F: (610)594-0829

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO8879Unique No:11002509Signed:Sean FeltonReport Date:30 Apr 2024

Contact/Location: JIM FEHR - VOLVO8879



CONSTRUCTION EQUIPMENT





