

CONSTRUCTION EQUIPMENT VOLVO A40G 353267 - HYDRAULIC SYSTEM



Sample No: VCP445605

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

SAMPLE IN	NFORMATION			
Sample Number		VCP445605	 	
Sample Date		25 Apr 2024	 	
Machine Hours		2215	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
Sample Status		ADNORIVIAL	 	
VOLVO				
OIL CONDI	TION			
Visc @ 40°C	cSt	45.3	 	
Acid Number (AN)	mg KOH/g	0.43	 	
VOLVO	IATION			
CONTAMIN				
Water	%	NEG	 	
Particles >4µm		14541	 	
Particles >6µm		■3949	 	
Particles >14µm		<u></u> 624	 	
ISO 4406:1999 (c)		21/19/16	 	
Silicon	ppm	4	 	
Sodium	ppm	■ 2	 	
Potassium	ppm	■ 2	 	
WEAR ME	ZIAT			
Iron		3	 	
Copper	ppm	■ <1	 	
Lead	ppm	= <1	 	
Tin	ppm	0	 	
Aluminum	ppm	2	 	
Chromium	ppm	0	 	
	ppm	3	 	
Molybdenum	ppm	_		
3		_	 	
Variacium	ррш	U	 	
VOLVO				
ADDITIVE:	2			
Calcium	ppm	115	 	
_			 	
Barium			 	
Nickel Titanium Silver Manganese Vanadium ADDITIVE Calcium Magnesium Zinc Phosphorus	ppm ppm ppm ppm ppm	0 0 0 0 0	 	



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

F: (239)481-3302

Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0090Unique No:11005001Signed:Wes DavisReport Date:01 May 2024



CONSTRUCTION EQUIPMENT





GRAPHS

