

CONSTRUCTION EQUIPMENT VULCAN VOLVO A40G 352007 - FRONT AXLE



Sample No: VCP430449

Oil Type: GEAR OIL SAE 80W90

Job No: VULCAN

SAMPLE	INFORMATIO	N		
Sample Number	_	VCP430449	 	
Sample Date		01 May 2024	 	
Machine Hours		7553	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
VOLVO	DITION			
OIL CON			 -	
Visc @ 40°C	cSt	140	 	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	 	
Silicon		 7	 	
Sodium	ppm	0	 	
Potassium	ppm	■ 2	 	
rotassium	ррпі	<u> </u>		
VOLVO				
WEAR N	METALS			
Iron	ppm	130	 	
Copper	ppm	6	 	
Lead	ppm	-<1	 	
Tin	ppm	■<1	 	
Aluminum	ppm	2	 	
Chromium	ppm	2	 	
Molybdenum	ppm	2	 	
Nickel	ppm	■ <1	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	■4	 	
Vanadium	ppm	<1	 	
ADDITIV	/ES			
Calcium		105	 	
Magnesium	ppm	105	 	
Zinc	ppm	■2	 	
Phosphorus	ppm	■ 39 ■ 1058	 	
Pnospnorus Barium	ppm	■ 0	 	
	ppm	245	 	
Boron	ppm	245	 	



SCOTT EQUIPMENT COMPANY LLC - Lavergne
1231 BRIDGESTONE PARKWAY
LAVERGNE, TN
US 37086
Contact: CLAY COULTER
CCOULTER@SCOTTCOMPANIES.COM
T: (615)793-3888
F: (615)793-9655

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0129Unique No:11009474Signed:Don BaldridgeReport Date:07 May 2024



CONSTRUCTION EQUIPMENT





