

CONSTRUCTION EQUIPMENT VOLVO A45G 353323 - BOGIE/CENTER AXLE



Sample No: VCP451247

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No:

SAMPLE	INFORMATIO	N		
Sample Number		VCP451247	VCP437504	
Sample Date		03 May 2024	12 Apr 2024	
Machine Hours		2406	2288	
Oil Hours		0	0	
Oil Changed		Not Changd	Not Changd	
Sample Status		ATTENTION	ATTENTION	
Sample Status		ATTENTION	ATTENTION	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	52.0	52.3	
VOLVO	AIN A TION			
_	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	4	■3	
Sodium	ppm	4	5	
Potassium	ppm	4	4	
WEAR N	AFTAI S			
_			- 450	
Iron	ppm	■285	158	
Copper	ppm	1	2	
Lead	ppm	2	0	
Tin	ppm	1	= <1	
Aluminum	ppm	= <1	0	
Chromium	ppm	■5	2	
Molybdenum	ppm	8	5	
Nickel	ppm	1	0	
Titanium	ppm	<1	0	
Silver	ppm	0	0	
Manganese	ppm	■9	6	
Vanadium	ppm	0	0	
VOLVO				
ADDITIV	ZES			
Calcium		101	□ 99	
	ppm	■ 101 ■ 14	1	
Magnesium Zinc	ppm	43	36	
	ppm	2418	2329	
Phosphorus Barium	ppm			
	ppm	0	0	
Boron	ppm	■234	293	



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

1.

F: (239)481-3302

Diagnosis

No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Additive levels indicate the addition of a different brand, or type of oil. Confirm oil type.

Depot:VOLVO0090Unique No:11016368Signed:Jonathan HesterReport Date:08 May 2024

Contact/Location: TODD LARK - VOLVO0090



CONSTRUCTION EQUIPMENT





