

CONSTRUCTION EQUIPMENT 25458 VOLVO A45G 342052 - REAR AXLE



Sample No: VCP422221

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

Job No: 25458

VOLVO	E INFORMATION	VI		
	INFURMATIU			
Sample Number		VCP422221	VCE254607	
Sample Date		01 May 2024	07 Dec 2018	
Machine Hours		8114	3852	
Oil Hours		0	3852	
Oil Changed		Changed	Not Changd	
Sample Status		NORMAL	NORMAL	
OIL CON	NITION			
			102.0	
Visc @ 40°C	cSt	■89.5	102.9	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	11	3	
Sodium	ppm	2		
Potassium	ppm	<u> </u>	0	
	ρρ			
VOLVO				
WEAR N	METALS			
Iron	ppm	129	1 9	
Copper	ppm	2	0	
Lead	ppm	1	0	
Tin	ppm	2	0	
Aluminum	ppm	2	0	
Chromium	ppm	■ 3	- <1	
Molybdenum	ppm	2	<1	
Nickel	ppm	1	0	
Titanium	ppm	<1	0	
Silver	ppm	0	<1	
Manganese	ppm	■ 3	<1	
Vanadium	ppm	0	0	
ADDITIV	/FC			
_		- 45	2	
Calcium	ppm	45	3	
Magnesium	ppm	4	<1	
Zinc	ppm	■36	3	
Phosphorus	ppm	493	1242	
Barium	ppm	0	0	



218 - ASCENDUM MACHINERY INC - N. CHARLESTON 7235 CROSS COUNTRY RD. NORTH CHARLESTON, SC US 29418 Contact: MATT MITCHAM matt.mitcham@ascendummachinery.com T:

F: (843)414-1129

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO3387Unique No:11016394Signed:Jonathan HesterReport Date:08 May 2024

33

ppm

Boron



CONSTRUCTION EQUIPMENT





