

CONSTRUCTION EQUIPMENT VFS VOLVO A40G 342633 - HYDRAULIC SYSTEM



Sample No: VCP446951

Oil Type: AW HYDRAULIC OIL ISO 46

Job No: VFS

VOLVO				
SAMPLE II	NFORMATION			
Sample Number	-	VCP446951	 	
Sample Date		29 Apr 2024	 	
Machine Hours		8195	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
OIL CONDI	TION			
Visc @ 40°C		= 42.6	 	
	cSt	43.6		
Acid Number (AN)	mg KOH/g	■ 0.42	 	
VOLVO				
CONTAMI	NATION			
Water	%	NEG	 	
Particles >4µm		3648	 	
Particles >6µm		420	 	
Particles > 14µm		16	 	
ISO 4406:1999 (c)		19/16/11	 	
Silicon	ppm	4	 	
Sodium	ppm	0	 	
Potassium	ppm	1	 	
WEAR ME	TALC			
	IMT7	_		
Iron	ppm	4	 	
Copper	ppm	1	 	
Lead	ppm	2	 	
Tin	ppm	■0	 	
Aluminum	ppm	2	 	
Chromium	ppm		 	
Molybdenum	ppm	■ <1	 	
Nickel	ppm	■0	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm		 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIVE:				
Calcium	ppm	2 4	 	
Magnesium	ppm	■30	 	
Zinc	ppm	■391	 	
Phosphorus	ppm	■338	 	
	- 1			



ROMCO INC

1350 NE LOOP 820 FORT WORTH, TX US 76106 Contact: CHRIS BITNER CBitner@romco.com T: F: (817)626-8983

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO0081Unique No:11017144Signed:Wes DavisReport Date:08 May 2024

0

0

ppm

ppm

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

