

# **CONSTRUCTION EQUIPMENT**

X18492 CANTON CONCR VOLVO L60H 621074 - HYDRAULIC SYSTE

Sample No: VCP443667

Silver

Manganese

Vanadium

Calcium

Zinc

Barium

Boron

Magnesium

Phosphorus

ppm

ppm

ppm

ppm

ppm

ppm

ppm

ppm

ppm

**ADDITIVES** 

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

**Job No:** X18492 CANTON CONCR

SAMPLE IN	NFORMATION			
_	-	VCP443667	 	
Sample Number				
Sample Date		06 May 2024	 	
Machine Hours		8110	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
VOLVO				
OIL CONDI	TION			
Visc @ 40°C	cSt	<b>41.0</b>	 	
Acid Number (AN)	mg KOH/g	■ 0.27	 	
CONTAMIN	MATION			
_				
Water	%	NEG	 	
Particles >4µm		5080	 	
Particles >6µm		■268	 	
Particles >14µm		<b>■</b> 16	 	
ISO 4406:1999 (c)		20/15/11	 	
Silicon	ppm	■8	 	
Sodium	ppm	<b>2</b>	 	
Potassium	ppm	<b>■</b> <1	 	
WEAR ME	TALS			
ron	ppm	<b>3</b>	 	
Copper	ppm	<u> </u>	 	
Lead	ppm	1	 	
Tin	ppm	<1	 	
Aluminum	ppm	<b>1</b>	 	
Chromium	ppm	<u></u> 2	 	
Molybdenum	ppm	<1	 	
Nickel	ppm	■0	 	
Titanium	ppm	0	 	
-		-		



### **SCOTT EQUIPMENT COMPANY LLC - Jackson**

3860 I-55 South JACKSON, MS US 39212

Contact: DWIGHT MCDOUGAL DMCDOUGAL@SCOTTCOMPANIES.COM

T:

F: (601)326-3359

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO8771Unique No:11019885Signed:Wes DavisReport Date:16 May 2024

**125** 

**451** 

**356** 

**-**<1

**-<1** 

**■**9



# **CONSTRUCTION EQUIPMENT**





#### GRAPHS

