

CONSTRUCTION EQUIPMENT VFS VOLVO A40G 342632 - BOGIE/CENTER AXLE



Sample No: VCP281769

Oil Type: GEAR OIL SAE 80W90

Job No: VFS

VOLVO CAMDIE	INFORMATION			
	INFUNMATION			
Sample Number		VCP281769	VCP348939	
Sample Date		29 Apr 2024	03 Feb 2022	
Machine Hours		7835	6440	
Oil Hours		0	0	
Oil Changed		Not Changd	Not Changd	
Sample Status		NORMAL	NORMAL	
OIL CON	DITION			
Visc @ 40°C	cSt	-40.2	E 40.3	
VISC @ 40 C	CSL	49.3	49.3	
VOLVO				
CONTAM	IINATION			
Water	%	NEG	NEG	
Silicon	ppm	■ 9	6	
Sodium	ppm	3	3	
Potassium	ppm	3	4	
	1-1-			
VOLVO	IETAL C			
WEAR M	IF I ALS			
Iron	ppm	■396	■300	
Copper	ppm	5	3	
Lead	ppm	0	< 1	
Tin	ppm	■0	- <1	
Aluminum	ppm	2	2	
Chromium	ppm	■ 4	3	
Molybdenum	ppm	7	6	
Nickel	ppm	2	2	
Titanium	ppm	<1	0	
Silver	ppm	0	0	
Manganese	ppm	■8	7	
Vanadium	ppm	<1	0	
ADDITIV	FS			
Calcium	-	□ 34	10	
	ppm		8	
Magnesium	ppm	■ 8	59	
Zinc	ppm	■ 62		
Phosphorus	ppm	■2476	2564	
Barium	ppm	0	0	
Boron	ppm	■83	37	



ROMCO INC

1350 NE LOOP 820 FORT WORTH, TX US 76106 Contact: CHRIS BITNER CBitner@romco.com T: F: (817)626-8983

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0081Unique No:11021918Signed:Sean FeltonReport Date:14 May 2024



CONSTRUCTION EQUIPMENT





