

Sample No: VCP377152

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No: X17147 WASTE CONN

VOLVO				
SAMPLE II	NFORMATION			
Sample Number	-	VCP377152	 	
Sample Date		09 May 2024	 	
Machine Hours		10782	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
OIL CONDI	TION			
Visc @ 40°C	cSt	40.1	 	
Acid Number (AN)		■ 0.54	 	
	9, 9	_ 0.0 .		
VOLVO	IATION			
CONTAMIN				
Water	%	NEG	 	
Particles >4µm		15544	 	
Particles >6µm		3477	 	
Particles > 14µm		<u> </u>	 	
ISO 4406:1999 (c)		21/19/15	 	
Silicon	ppm	= <1	 	
Sodium	ppm	1	 	
Potassium	ppm	■0	 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	0	 	
Copper	ppm	0	 	
Lead	ppm	0	 	
Tin	ppm	-<1	 	
Aluminum	ppm	0	 	
Chromium	ppm	■ <1	 	
Molybdenum	ppm	0	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	■ 0	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIVE:	<u></u>			
Calcium	ppm	297	 	
Magnesium	ppm	■ 5	 	
Zinc	ppm	767	 	
Phosphorus	ppm	600	 	
Barium	ppm	1	 	
Boron	ppm	0	 	



WISE HEAVY EQUIPMENT

9229 S 97TH ST LA VISTA, NE US 68128 Contact: JASON HASSLER jhassler@wiseheavyequipment.com T: F: (402)597-0865

Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0182Unique No:11029965Signed:Wes DavisReport Date:15 May 2024



CONSTRUCTION EQUIPMENT





GRAPHS

