

CONSTRUCTION EQUIPMENT HOLIDAY SAND VOLVO A45G 752256 - FRONT AXLE



Sample No: VCE173509

Oil Type: VOLVO API GL-5 SAE 75W90

Job No: HOLIDAY SAND

SAMPLE	INFORMATION			
Sample Number		VCE173509		
Sample Date		03 May 2024		
Machine Hours		577		
Oil Hours		0		
Oil Changed		Changed		
Sample Status		NORMAL		
VOLVO	DITION			
OIL CON			<u> </u>	
Visc @ 40°C	cSt	54.8		
VOLVO				
CONTAN	MINATION			
Water	%	NEG		
Silicon		MEG ■4		
Sodium	ppm	2		
Potassium	ppm	4		
rotassium	ррпп	-		
VOLVO				
WEAR N	METALS			
Iron	ppm	62		
Copper	ppm	■ 1		
Lead	ppm	■<1		
Tin	ppm	■<1		
Aluminum	ppm	2		
Chromium	ppm	1		
Molybdenum	ppm	14		
Nickel	ppm	■<1		
Titanium	ppm	<1		
Silver	ppm	<1		
Manganese	ppm	6		
Vanadium	ppm	<1		
VOLVO				
ADDITIV	/ES			
Calcium	ppm	169		
Magnesium	ppm	16		
Zinc	ppm	65		
Phosphorus	ppm	2761		
Barium	ppm	0		
Boron	ppm	262		



GW VAN KEPPEL CO 1801 NORTH 9TH ST KANSAS CITY, KS US 66110 Contact: PAT SAUSE psause@vankeppel.com T:

F: (913)281-4815

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:GWVKANUnique No:11032073Signed:Jonathan HesterReport Date:18 May 2024

Contact/Location: PAT SAUSE - GWVKAN



CONSTRUCTION EQUIPMENT





