

CONSTRUCTION EQUIPMENT

56538 MCLAMB VOLVO A30G 752017 - REAR RIGHT FINAL DRIVE

Sample No: VCP436546

Oil Type: GEAR OIL SAE 80W90

Job No: 56538 MCLAMB

VOLVO	LINEODMATIO	V		
	E INFORMATIO			
Sample Number		VCP436546	 	
Sample Date		15 May 2024	 	
Machine Hours		4808	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		SEVERE	 	
OIL CON	IDITION			
Visc @ 40°C	cSt	127	 	
VOLVO				
CONTAR	MINATION			
Water	%	▲ 1.21	 	
Silicon	ppm	▲ 8779	 	
Sodium	ppm	■ 12	 	
Potassium	ppm	122	 	
rotassium	ρριτι	<u> </u>		
VOLVO				
WEAR I	METALS			
Iron	ppm	▲ 10248	 	
Copper	ppm	2445	 	
Lead	ppm	■ 3	 	
Tin	ppm	122	 	
Aluminum	ppm	1449	 	
Chromium	ppm	120	 	
Molybdenum	ppm	■8	 	
Nickel	ppm	▲ 90	 	
Titanium	ppm	147	 	
Silver	ppm	<1	 	
Manganese	ppm	78	 	
Vanadium	ppm	5	 	
	ρρ			
VOLVO	VIDE .		 	
ADDITIV	AFZ			
Calcium	ppm	■84	 	
Magnesium	ppm	49	 	
Zinc	ppm	65	 	
Phosphorus	ppm	739	 	
Barium	ppm	0	 	
Boron	ppm	105	 	



113 - ASCENDUM MACHINERY INC - GARNER
3561 JONES SAUSAGE ROAD
GARNER, NC
US 27529
Contact: JACOB MARTIN
JACOB.MARTIN@ASCENDUMMACHINERY.COM
T:
F: (919)661-9038

Diagnosis

We advise that you check all areas where dirt can enter the system. We advise that you check for the source of water entry. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.Bearing and/or gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. There is a high concentration of water present in the oil. The oil is no longer serviceable due to the presence of contaminants.

 Depot:
 VOLVO0157

 Unique No:
 11033045

 Signed:
 Sean Felton

 Report Date:
 20 May 2024



CONSTRUCTION EQUIPMENT





