

# CONSTRUCTION EQUIPMENT VOLVO A40G 352497 - HYDRAULIC SYSTEM



Sample No: VCP451100

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

SAMPLE II	NFORMATION				
Sample Number		VCP451100			
Sample Date		16 May 2024			
Machine Hours		5924			
Oil Hours		0			
Oil Changed		Not Changd			
Sample Status		ABNORMAL			
OIL CONDITION					
Visc @ 40°C	cSt	<b>44.8</b>			
Acid Number (AN)	mg KOH/g	■ 0.33			
VOLVO					
CONTAMINATION					
Water	%	NEG			
Particles >4µm	70	25518			
Particles >6µm		8192			
Particles > 14µm		△ 552			
ISO 4406:1999 (c)		22/20/16			
Silicon	ppm	<b>■ 17</b>			
Sodium	ppm	<b>1</b>			
Potassium	ppm	 0			
T Otassiani	PPIII				
VOLVO					
WEAR METALS					
Iron	ppm	<b>13</b>			
Copper	ppm	■3			
Lead	ppm	■4			
Tin	ppm	■0			
Aluminum	ppm	■9			
Chromium	ppm	<b>■</b> <1			
Molybdenum	ppm	■0			
Nickel	ppm	■0			
Titanium	ppm	<1			
Silver	ppm	0			
Manganese	ppm	<b>0</b>			
Vanadium	ppm	0			
VOLVO					
ADDITION					
Calcium	ppm	■80			
Magnesium	ppm	<b>4</b>			
Zinc	ppm	<b>422</b>			
Phosphorus	ppm	■328			
Barium	ppm	■0			
Boron	ppm	<b>0</b>			



### **ALTA EQUIPMENT COMPANY**

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

F: (239)481-3302

## Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

 Depot:
 VOLVO0090

 Unique No:
 11035540

 Signed:
 Wes Davis

 Report Date:
 21 May 2024



# **CONSTRUCTION EQUIPMENT**





#### GRAPHS

