

CONSTRUCTION EQUIPMENT RSO-038028 HITACHI 060320 - REAR LEFT FINAL DRIVE



Sample No: VCP447622

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No: RSO-038028

VOLVO CAMDIE	INFORMATION	N		
	. IMI UMPIATIUI			_
Sample Number		VCP447622	 	
Sample Date		10 May 2024	 	
Machine Hours		270	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
OIL CON	DITION			
Visc @ 40°C	cSt	□ 186	 	
VISC @ 40 C	CSL	100	 	
VOLVO				
CONTAN	MINATION			
Water	%	NEG	 	
Silicon	ppm	22	 	
Sodium	ppm	2	 	
Potassium	ppm	4	 	
	ррпп	— •		
VOLVO				
WEAR N	METALS			
Iron	ppm	■ 94	 	
Copper	ppm	-<1	 	
Lead	ppm	0	 	
Tin	ppm	■ 0	 	
Aluminum	ppm	■ 0	 	
Chromium	ppm	■ 4	 	
Molybdenum	ppm	■ 0	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	7	 	
Vanadium	ppm	<1	 	
VOLVO	IFC			
ADDITIV	JE2			
Calcium	ppm	16	 	
Magnesium	ppm	■ 0	 	
Zinc	ppm	7	 	
Phosphorus	ppm	566	 	
Barium	ppm	1	 	
-		_440		



SAIIA CONSTRUCTION LLC

4400 LEWISBURG RD BIRMINGHAM, AL US 35207 Contact: STEPHANI BRITTON

sbritton@saiia.com;doug.bogart@wearcheck.com

T: (205)943-2268 F: (205)943-2269

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:SAIBIRUnique No:11036008Signed:Sean FeltonReport Date:22 May 2024

ppm

110

Boron



CONSTRUCTION EQUIPMENT





