

## CONSTRUCTION EQUIPMENT X14147 VOLVO A25G 752640 - FRONT AXLE



Sample No: VCP399044

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

**Job No:** X14147

ZAMPI F	INFORMATION	N		
		VCP399044	 	
Sample Number				
Sample Date		17 May 2024	 	
Machine Hours		1400	 	
Oil Hours		500		
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	<b>87.3</b>	 	
VOLVO	UNIA TION			
LONTAM	IINATION			
Water	%	NEG	 	
Silicon	ppm	<b>6</b>	 	
Sodium	ppm	<b>■&lt;1</b>	 	
Potassium	ppm	<b>■</b> 5	 	
WEAR M	ETALC			
_				
Iron	ppm	■278	 	
Copper	ppm	<b>40</b>	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	■2	 	
Aluminum	ppm	<b>■&lt;1</b>	 	
Chromium	ppm	■5	 	
Molybdenum	ppm	■9	 	
Nickel	ppm	■3	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>9</b>	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIV	ES			
Calcium	ppm	<b>□</b> 786	 	
Magnesium	ppm	■0	 	
Zinc	ppm	<b>■351</b>	 	
Phosphorus	ppm	■1324	 	
Barium	ppm	■0	 	
Boron	ppm	■243	 	
DOIOII	ppili		 	



SCOTT EQUIPMENT COMPANY LLC - Broussard
100 IDA ROAD
BROUSSARD, LA
US 70518
Contact: ALISON HARGRODER
ahargroder@scottcompanies.com
T: (337)837-2907
F: (337)837-5116

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO6241Unique No:11044781Signed:Sean FeltonReport Date:24 May 2024



## **CONSTRUCTION EQUIPMENT**





