

CONSTRUCTION EQUIPMENT 716570 VOLVO L25H 1420334 - FRONT AXLE



Sample No: VCP449897

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: 716570

VOLVO	INCODMATION	J			
	INFORMATION				_
Sample Number		VCP449897			
Sample Date		22 May 2024			
Machine Hours		1540			
Oil Hours		1540			
Oil Changed		Changed			
Sample Status		ATTENTION			
OIL CONDITION					
Visc @ 40°C	cSt	63.3			
		• • • • • • • • • • • • • • • • • • • •			
VOLVO					
CONTAM	IINATION				
Water	%	NEG			
Silicon	ppm	■18			
Sodium	ppm	17			
Potassium	ppm	5			
VOLVO	IETAL C				
WEAR M	IE I ALS				
Iron	ppm	■ 205			
Copper	ppm	4			
Lead	ppm	■<1			
Tin	ppm	■0			
Aluminum	ppm	2			
Chromium	ppm	■3			
Molybdenum	ppm	■<1			
Nickel	ppm	■<1			
Titanium	ppm	<1			
Silver	ppm	<1		***	
Manganese	ppm	11			
Vanadium	ppm	<1			
ADDITIV	IES				
Calcium	ppm	3507			
Magnesium	ppm	■12			
Zinc	ppm	1439			
Phosphorus	ppm	1439			
Barium		0			
Boron	ppm	■ 124			
DOION	ppm	124			



CADILLAC ASPHALT PAVING LLC

2575 HAGGERTY ROAD CANTON, MI US 48188 Contact: SERVICE MANAGER

T: (734)394-0261 F:

Diagnosis

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. This plus the additive levels indicates the addition of a different brand, or type of oil. Confirm oil type.

Depot:CADCANUnique No:11049301Signed:Don BaldridgeReport Date:30 May 2024



CONSTRUCTION EQUIPMENT





GRAPHS

