

CONSTRUCTION EQUIPMENT 25772 VOLVO A45G 352721 - REAR AXLE



Sample No: VCP447695

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

Job No: 25772

| VOLVO | INFORMATIO | M | | |
|----------------|------------|--------------|------|--|
| | INFORMATIO | N | | |
| Sample Number | | VCP447695 | | |
| Sample Date | | 23 May 2024 | | |
| Machine Hours | | 4065 | | |
| Oil Hours | | 0 | | |
| Oil Changed | | Changed | | |
| Sample Status | | NORMAL | | |
| | | | | |
| VOLVO OII CON | DITION | | | |
| OIL CON | | | | |
| Visc @ 40°C | cSt | 49.2 | | |
| VOLVO | | | | |
| CONTAN | IINATION | | | |
| _ | | NEC | | |
| Water | % | NEG | | |
| Silicon | ppm | 4 | | |
| Sodium | ppm | - <1 | | |
| Potassium | ppm | - <1 | | |
| VOLVO | | | | |
| WEAR M | IETALS | | | |
| Iron | ppm | □ 293 | | |
| Copper | ppm | ■37 | | |
| Lead | ppm | = <1 | | |
| Tin | ppm | 0 | | |
| Aluminum | | ■0 | | |
| Chromium | ppm | 2 | | |
| | ppm | 2 | | |
| Molybdenum | ppm | _ | | |
| Nickel | ppm | 0 | | |
| Titanium | ppm | 0 | | |
| Silver | ppm | 0 | | |
| Manganese | ppm | 10 | | |
| Vanadium | ppm | 0 | | |
| VOLVO | | | | |
| ADDITIV | ES | | | |
| Calcium | ppm | 108 | | |
| Magnesium | ppm | ■0 | | |
| Zinc | | ■ 65 | | |
| Phosphorus | ppm | 2491 | | |
| Barium | ppm | 0 | | |
| | ppm | _ | | |
| Boron | ppm | 249 | | |



218 - ASCENDUM MACHINERY INC - N. CHARLESTON 7235 CROSS COUNTRY RD. NORTH CHARLESTON, SC US 29418 Contact: MATT MITCHAM matt.mitcham@ascendummachinery.com T:

F: (843)414-1129

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO3387Unique No:11056514Signed:Jonathan HesterReport Date:31 May 2024



CONSTRUCTION EQUIPMENT





