

CONSTRUCTION EQUIPMENT VOLVO A45G 352787 - HYDRAULIC SYSTEM



Sample No: VCP441589

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

VOLVO				
SAMPLE II	NFORMATION			
Sample Number	-	VCP441589	 	
Sample Date		30 May 2024	 	
Machine Hours		5058	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		ABNORMAL	 	
OIL CONDI	TION			
Visc @ 40°C	cSt	49.5	 	
Acid Number (AN)		■ 0.45	 	
Acid Ivalliber (7114)	mg Kon/g	<u> </u>		
VOLVO	VATION			
CONTAMIN	NATIUN			
Water	%	NEG	 	
Particles >4µm		30904	 	
Particles >6µm		<u> </u>	 	
Particles >14µm		<u>▲</u> 745	 	
ISO 4406:1999 (c)		22/21/17	 	
Silicon	ppm	■ 9	 	
Sodium	ppm	2	 	
Potassium	ppm	■0	 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	2	 	
Copper	ppm	2	 	
Lead	ppm	■0	 	
Tin	ppm	■0	 	
Aluminum	ppm	■5	 	
Chromium	ppm	<u> </u>	 	
Molybdenum	ppm	■0	 	
Nickel	ppm	■0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	0	 	
Vanadium	ppm	0	 	
ADDITIVE	ξ			
_		442		
Calcium	ppm	443	 	
Magnesium	ppm	■ 3	 	
Zinc	ppm	■ 526	 	
Phosphorus	ppm	427	 	
Barium	ppm	0	 	
Boron	ppm	■ 0	 	



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK

tlark@altaequipfl.com T:

F: (239)481-3302

Diagnosis

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0090Unique No:11059688Signed:Wes DavisReport Date:04 Jun 2024

Contact/Location: TODD LARK - VOLVO0090



CONSTRUCTION EQUIPMENT





GRAPHS

