

CONSTRUCTION EQUIPMENT 136502 VOLVO A40G 752154 - HYDRAULIC SYSTEM



Sample No: VCP447665

Oil Type: AW HYDRAULIC OIL ISO 46

Job No: 136502

SAMPLE II	NFORMATION			
Sample Number		VCP447665	VCP442493	
·		07 Jun 2024		
Sample Date Machine Hours		880	03 Apr 2024 530	
Oil Hours		0	0	
Oil Changed		Not Changd	Not Changd	
_		NORMAL	NORMAL	
Sample Status		NORWAL	NORIVIAL	
VOLVO				
OIL CONDI	TION			
Visc @ 40°C	cSt	45.1	45.4	
Acid Number (AN)	mg KOH/g	■ 0.42	0.43	
CONTAMI	NATION			
CONTAMIN				
Water	%	NEG	NEG	
Particles >4µm		674	500	
Particles >6µm		176	140	
Particles >14µm		11	1 2	
ISO 4406:1999 (c)		17/15/11	16/14/11	
Silicon	ppm	2	- <1	
Sodium	ppm	■ 0	0	
Potassium	ppm	■<1	1	
WEAR ME	7147			
_				
Iron	ppm	2	1	
Copper	ppm	2	2	
Lead	ppm	1	<1	
Tin Aluminum	ppm	■ <1	= <1	
	ppm	2	2	
Chromium	ppm	■ <1	<1	
Molybdenum Nickel	ppm	0	0	
	ppm	■0	0	
Titanium	ppm	<1	<1	
Silver	ppm	0	<1	
Manganese	ppm	0	0	
Vanadium	ppm	0	<1	
VOLVO				
ADDITIVE:				
Calcium	ppm	■89	98	
Magnesium	ppm	1	<1	
Zinc	ppm	436	447	
Phosphorus	ppm	302	358	
Barium	ppm	0	<1	
-	PPIII		2.1	



LATTIMORE MATERIALS/HOLCIM - ROSSER - LAFARGE
14242 S SH-34
SCURRY, TX
US 75158
Contact: WALLACE WARREN
wallace.warren@lafargeholcim.com
T:
F:

Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) AW HYDRAULIC OIL ISO 46. Please confirm.

All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:LATSCUUnique No:11075182Signed:Wes DavisReport Date:13 Jun 2024

Contact/Location: WALLACE WARREN - LATSCU

ppm

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

