

## CONSTRUCTION EQUIPMENT 136502 VOLVO A40G 752154 - BRAKE



Sample No: VCP442484
Oil Type: {unknown}
Job No: 136502

| VOLVO CAMDIF  | INFORMATION  |               |               |          |
|---------------|--------------|---------------|---------------|----------|
|               | INI UNMATION |               | VCD 420722    | <u>.</u> |
| Sample Number |              | VCP442484     | VCP439723     | <br>     |
| Sample Date   |              | 07 Jun 2024   | 07 Apr 2024   | <br>     |
| Machine Hours |              | 880           | 530           | <br>     |
| Oil Hours     |              | 0             | 0             | <br>     |
| Oil Changed   |              | Not Changd    | Not Changd    | <br>     |
| Sample Status |              | NORMAL        | NORMAL        | <br>     |
| VOLVO         |              |               |               |          |
| OIL CON       | DITION       |               |               |          |
| Visc @ 40°C   | cSt          | <b>43.5</b>   | <b>1</b> 43.6 | <br>     |
| VISC & 40 C   | CSC          | <b>-</b> 43.3 |               |          |
| VOLVO         |              |               |               |          |
| CONTAM        | INATION      |               |               |          |
| Water         | %            | NEG           | NEG           | <br>     |
| Silicon       | ppm          | <b>12</b>     | <b>1</b> 0    | <br>     |
| Sodium        | ppm          | <b>■&lt;1</b> | <b>4</b>      | <br>     |
| Potassium     | ppm          | <b>4</b>      | <b>1</b>      | <br>     |
|               |              |               |               |          |
| VOLVO         | ETALC        |               |               |          |
| WEAR M        | F1AL2        |               |               |          |
| Iron          | ppm          | <b>15</b>     | <b>7</b>      | <br>     |
| Copper        | ppm          | <b>54</b>     | <b>1</b> 7    | <br>     |
| Lead          | ppm          | <b></b>       | <b>0</b>      | <br>     |
| Tin           | ppm          | <b>■&lt;1</b> | <b>-</b> <1   | <br>     |
| Aluminum      | ppm          | <b>2</b>      | <b>0</b>      | <br>     |
| Chromium      | ppm          | <b>■</b> <1   | <b>0</b>      | <br>     |
| Molybdenum    | ppm          | <1            | 0             | <br>     |
| Nickel        | ppm          | ■3            | <b>1</b>      | <br>     |
| Titanium      | ppm          | <1            | 0             | <br>     |
| Silver        | ppm          | 0             | 0             | <br>     |
| Manganese     | ppm          | <1            | <1            | <br>     |
| Vanadium      | ppm          | 0             | 0             | <br>     |
|               | -            |               |               |          |
| ADDITIV       | IEC          |               |               | <br>     |
|               | D            |               |               |          |
| Calcium       | ppm          | 3722          | 3762          | <br>     |
| Magnesium     | ppm          | 6             | 8             | <br>     |
| Zinc          | ppm          | 1557          | 1578          | <br>     |
| Phosphorus    | ppm          | 1214          | 1288          | <br>     |
| Barium        | ppm          | 0             | 0             | <br>     |
| Boron         | ppm          | 143           | 124           | <br>     |
|               |              |               |               |          |



LATTIMORE MATERIALS/HOLCIM - ROSSER - LAFARGE 14242 S SH-34 SCURRY, TX US 75158 Contact: WALLACE WARREN wallace.warren@lafargeholcim.com T: F:

## Diagnosis

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.All component wear rates are normal. There is no indication of any contamination in the fluid. The condition of the fluid is acceptable for the time in service.

Depot:LATSCUUnique No:11075567Signed:Don BaldridgeReport Date:14 Jun 2024



## **CONSTRUCTION EQUIPMENT**





