Sample No: VCP454863

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

**Job No:** 716661 MOSAIC

SAMPLE	INFORMATION			
Sample Number	<u> </u>	VCP454863	 	
Sample Date		22 May 2024	 	
Machine Hours		1348	 	
Oil Hours		500	 	
Oil Changed		Changed	 	
Sample Status		ABNORMAL	 	
		71271071111111		
VOLVO	DITION			
OIL CON	DITION			
Visc @ 40°C	cSt	<b>196</b>	 	
CUNTAN	IINATION			
_		NEO.		
Water	%	NEG	 	
Silicon	ppm	<u> </u>	 	
Sodium	ppm	<b>4</b>	 	
Potassium	ppm	<b>2</b>	 	
VOLVO				
WEAR N	<b>TETALS</b>			
Iron	ppm	<u></u> 977	 	
Copper	ppm	<u>2</u>	 	
Lead	ppm	0	 	
Tin	ppm	0	 	
Aluminum	ppm	<b>1</b> 1	 	
Chromium	ppm	<b>1</b> 9	 	
Molybdenum	ppm	<b>2</b>	 	
Nickel	ppm	<b>2</b>	 	
Titanium	ppm	1	 	
Silver	ppm	0	 	
Manganese	ppm	<b>10</b>	 	
Vanadium		<1	 	
variaciditi	ppm	<b>\</b> 1		
VOLVO				
ADDITI\	ES			
Calcium	ppm	■96	 	
Magnesium	ppm	 8	 	
Zinc	ppm	<b>55</b>	 	
Phosphorus	ppm	<u>579</u>	 	
Barium	ppm	<b>4</b>	 	
Boron	ppm	<b>44</b>	 	

ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
8418 PALM RIVER ROAD
TAMPA, FL
US 33619
Contact: JOHN FARDELLA
john.fardella@altg.com
T: (813)630-0077
F: (813)630-2233

## Diagnosis

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0093Unique No:11087967Signed:Sean FeltonReport Date:21 Jun 2024



## **CONSTRUCTION EQUIPMENT**





