

CONSTRUCTION EQUIPMENT RSO-038391 HITACHI 060320 - RIGHT SWING DRIVE



Sample No: VCP443963

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No: RSO-038391

LAMPI	E INFORMATION	l e		
			VCD 447620	
Sample Number		VCP443963	VCP447620	
Sample Date		20 Jun 2024	10 May 2024	
Machine Hours		530	270	
Oil Hours		0	0	
Oil Changed		Not Changd	Changed	
Sample Status		NORMAL	NORMAL	
VOLVO				
OIL CON	IDITION			
Visc @ 40°C	cSt	263	189	
V13C @ 40 C	CSt			
VOLVO				
CONTAI	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	11	1 4	
Sodium	ppm	1	2	
Potassium	ppm	■<1	6	
VOLVO	METALS			
WEAR	ME I ALS			
Iron	ppm	■31	149	
Copper	ppm	■12	2	
Lead	ppm	■0	□0	
Tin	ppm	■ 0	0	
Aluminum	ppm	■0	< 1	
Chromium	ppm	■<1	2	
Molybdenum	ppm	■ 3	0	
Nickel	ppm	■ 0	0	
Titanium	ppm	0	0	
Silver	ppm	0	0	
Manganese	ppm	■ <1	4	
Vanadium	ppm	0	<1	
ADDITI	VES			
Calcium	ppm	175	1 4	
Magnesium	ppm	27	0	
Zinc	ppm	■ 126	1 0	
Phosphorus		832	608	
Barium	ppm	■ <1	000	
Darium	ppiii	= 110		



SAIIA CONSTRUCTION LLC

4400 LEWISBURG RD BIRMINGHAM, AL US 35207 Contact: STEPHANI BRITTON

sbritton@saiia.com;doug.bogart@wearcheck.com

T: (205)943-2268 F: (205)943-2269

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:SAIBIRUnique No:11099798Signed:Angela BorellaReport Date:28 Jun 2024

118

Boron



CONSTRUCTION EQUIPMENT





