



CONSTRUCTION EQUIPMENT

592764 HERC VOLVO EC350EL 3 10708 - REAR RIGHT FINAL DRIVE



Sample No: VCP443809
Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5
Job No: 592764 HERC



SAMPLE INFORMATION

Sample Number	VCP443809	---	---	---
Sample Date	01 Jul 2024	---	---	---
Machine Hours	3516	---	---	---
Oil Hours	0	---	---	---
Oil Changed	Not Chngd	---	---	---
Sample Status	SEVERE	---	---	---

ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
 8418 PALM RIVER ROAD
 TAMPA, FL
 US 33619
 Contact: KENNY HANEY
 khaney@flaglerce.com
 T: (813)630-0077
 F: (813)630-2233



OIL CONDITION

Visc @ 40°C	cSt	■ 219	---	---	---
-------------	-----	-------	-----	-----	-----



CONTAMINATION

Water	%	NEG	---	---	---
Silicon	ppm	▲ 721	---	---	---
Sodium	ppm	■ 6	---	---	---
Potassium	ppm	■ 5	---	---	---



WEAR METALS

Iron	ppm	▲ 4366	---	---	---
Copper	ppm	■ 8	---	---	---
Lead	ppm	■ <1	---	---	---
Tin	ppm	■ 0	---	---	---
Aluminum	ppm	● 64	---	---	---
Chromium	ppm	▲ 78	---	---	---
Molybdenum	ppm	■ 8	---	---	---
Nickel	ppm	■ 6	---	---	---
Titanium	ppm	5	---	---	---
Silver	ppm	0	---	---	---
Manganese	ppm	■ 37	---	---	---
Vanadium	ppm	<1	---	---	---



ADDITIVES

Calcium	ppm	■ 66	---	---	---
Magnesium	ppm	■ 10	---	---	---
Zinc	ppm	■ 28	---	---	---
Phosphorus	ppm	■ 393	---	---	---
Barium	ppm	■ 2	---	---	---
Boron	ppm	■ 0	---	---	---

Diagnosis

We advise that you check all areas where dirt can enter the system. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The oil is no longer serviceable due to the presence of contaminants.

Depot: VOLVO0093
Unique No: 11112498
Signed: Sean Felton
Report Date: 09 Jul 2024



CONSTRUCTION EQUIPMENT



GRAPHS

