

CONSTRUCTION EQUIPMENT VOLVO A40G 352909 - BOGIE/CENTER AXLE



Sample No: VCP454374

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No:

VOLVO SAMPLE	INFORMATION			
Sample Number		VCP454374	VCP438339	
Sample Date		02 Jul 2024	01 Mar 2024	
Machine Hours		1326	4219	
		0	4219	
Oil Hours				
Oil Changed		Changed	Changed	
Sample Status		NORMAL	NORMAL	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	54.1	49.5	
VISC @ 40 C	CSt	3 7.1		
VOLVO				
CONTAN	MINATION			
Water	%	NEG	NEG	
Silicon	ppm	2	1 9	
Sodium	ppm	■ 3	■ 3	
Potassium	ppm	■ 3	5	
		_	_	
VOLVO	AFTALC			
WEAR N	NETAL2			
Iron	ppm	143	589	
Copper	ppm	■ 3	4	
Lead	ppm	■<1	0	
Tin	ppm	■ 0	- <1	
Aluminum	ppm	■<1	4	
Chromium	ppm	1	8	
Molybdenum	ppm	2	■ 8	
Nickel	ppm		3	
Titanium	ppm	0	<1	
Silver	ppm	0	0	
Manganese	ppm	5	2 0	
Vanadium	ppm	0	<1	
	pp			
VOLVO	IFC			
ADDITIV	IFZ.			
Calcium	ppm	191	5 0	
Magnesium	ppm	2	4	
Zinc	ppm	■80	■27	
Phosphorus	ppm	2584	2463	
Barium	ppm	0	0	
Boron	ppm	249	160	
	- - · · ·			



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

T:

F: (239)481-3302

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Confirm oil type. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0090Unique No:11114030Signed:Don BaldridgeReport Date:10 Jul 2024



CONSTRUCTION EQUIPMENT





