

CONSTRUCTION EQUIPMENT VOLVO EC350EL 314565 - HYDRAULIC SYSTEM



Sample No: VCP451116

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

VOLVO				
SAMPLE II	NFORMATION			
Sample Number	-	VCP451116	 	
Sample Date		08 Jul 2024	 	
Machine Hours		1809	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
VOLVO	TION			
OIL CONDI	IIUN			
Visc @ 40°C	cSt	44.4	 	
Acid Number (AN)	mg KOH/g	■ 0.52	 	
CONTAMIN	ΙΔΤΙΩΝ			
_		NEC		
Water	%	NEG	 	
Particles >4µm		<u>^</u> 23761	 	
Particles >6µm		▲ 5275	 	
Particles >14µm		314	 	
ISO 4406:1999 (c)		22/20/15	 	
Silicon	ppm	4	 	
Sodium	ppm	2	 	
Potassium	ppm	2	 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	□ 3	 	
Copper	ppm	17	 	
Lead	ppm	■0	 	
Tin	ppm	■<1	 	
Aluminum	ppm		 	
Chromium	ppm	■0	 	
Molybdenum	ppm	■0	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	0	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIVE	7			
Calcium	ppm	■82	 	
Magnesium	ppm	2	 	
Zinc	ppm	■538	 	
Phosphorus	ppm	446	 	
Barium	ppm	■0	 	
Boron	ppm	■ 0	 	

ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

1:

F: (239)481-3302

Diagnosis

The filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0090Unique No:11115735Signed:Wes DavisReport Date:11 Jul 2024



CONSTRUCTION EQUIPMENT





GRAPHS

