

## **CONSTRUCTION EQUIPMENT**

HERC RENTALS VOLVO L110H 632557 - HYDRAULIC SYSTEM

Sample No: VCP443575

Particles > 14µm

ISO 4406:1999 (c)

ppm

ppm

ppm

Silicon

Sodium

Potassium

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

**39** 

**2** 

**3** 

**■**0

22/20/12

Job No: HERC RENTALS

SAMPLE INFORMATION								
Sample Number		VCP443575						
Sample Date		09 Jul 2024						
Machine Hours		2420						
Oil Hours		0						
Oil Changed		Not Changd						
Sample Status		ABNORMAL						
OIL CONDIT	LIUN							
OIL CONDI	IUN							
Visc @ 40°C	cSt	<b>43.2</b>						
Acid Number (AN)	mg KOH/g	■ 0.34						
CONTAMIN	IATION							
LUNTAMIR	ATION							
Water	%	NEG						
Particles >4µm		36543						
Particles >6µm		<b>△</b> 6570						

VOLVO	METALC			
WEAK	METALS			
Iron	ppm	<b>■</b> 5	 	
Copper	ppm	<b>2</b>	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>■</b> 0	 	
Aluminum	ppm	<b>0</b>	 	
Chromium	ppm	<b>■</b> <1	 	
Molybdenum	ppm	<b>■&lt;1</b>	 	
Nickel	ppm	<b>■</b> 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>0</b>	 	
Vanadium	ppm	0	 	

ADDITIVES							
Calcium	ppm	<b>68</b>					
Magnesium	ppm	■2					
Zinc	ppm	■380					
Phosphorus	ppm	■312					
Barium	ppm	<b>0</b>					
Boron	ppm	■0					



ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
8418 PALM RIVER ROAD
TAMPA, FL
US 33619
Contact: KENNY HANEY
khaney@flaglerce.com
T: (813)630-0077
F: (813)630-2233

## Diagnosis

The filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0093Unique No:11123624Signed:Wes DavisReport Date:15 Jul 2024



## **CONSTRUCTION EQUIPMENT**





## GRAPHS

