



VOLVO PENTA 3940023450 - PORT IPS

Sample No: VPA056407

Oil Type: VOLVO API GL-5 SAE 75W90

| SAMPLE INFORM | IATION | | | |
|---------------|----------|---------------|------|--|
| | INTION | | | |
| Sample Number | | VPA056407 | | |
| Sample Date | | 03 Jul 2023 | | |
| Machine Hours | | 704 | | |
| Oil Hours | | 0 | | |
| Oil Changed | | Not Changd | | |
| Sample Status | | ATTENTION | | |
| OIL CONDITION | | | | |
| Visc @ 40°C | cSt | 107 | | |
| CONTAMINATION | 1 | | | |
| Silicon | ppm | 15 | | |
| Sodium | ppm | ■38 | | |
| Potassium | ppm | ■ 2 | | |
| | ррш | | | |
| WEAR METALS | | | | |
| PQ | | 10 | | |
| Iron | ppm | ^ 256 | | |
| Copper | ppm | 28 | | |
| Lead | ppm | 0 | | |
| Tin | ppm | 0 | | |
| Aluminum | ppm | 11 | | |
| Chromium | ppm | 2 | | |
| Molybdenum | ppm | ■ <1 | | |
| Nickel | ppm | 4 | | |
| Titanium | ppm | 0 | | |
| Silver | ppm | 0 | | |
| Manganese | ppm | 1 4 | | |
| Vanadium | ppm | 0 | | |
| ADDITIVES | | | | |
| | 10.10.17 | =12 | | |
| Calcium | ppm | 13 | | |
| Magnesium | ppm | 4 | | |
| Zinc | ppm | ■54 | | |
| Phosphorus | ppm | ■ 1388 | | |
| Barium | ppm | 0 | | |
| Boron | ppm | 285 | | |

FDDA FT PIERCE - POWER CENTER

FORT PIERCE, FL US Contact: KYLE GRASER k.graser@ssss.com T: F:

Diagnosis

No corrective action is recommended at this time. Resample at the next service interval to monitor. Gear wear is indicated. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP208659Unique No:10562946Signed:Jonathan HesterReport Date:20 Jul 2023





