



RUN RATE ZF 20322390 - INBOARD - PORT GEARBOX

Sample No: VPA056440
Oil Type: SAE 30W

CAMPLE INCOPAL	TION			
SAMPLE INFORMA	ATIUN			
Sample Number		VPA056440	 	
Sample Date		31 Aug 2023	 	
Machine Hours		339	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
OIL CONDITION				
Visc @ 40°C	cSt	■84.6	 	
CONTAMINATION				
CONTAMINATION				
Silicon	ppm	■ 9	 	
Sodium	ppm	7	 	
Potassium	ppm	2	 	
WEAR METALS				
PQ		62	 	
Iron	ppm	■94	 	
Copper	ppm	■ 111	 	
Lead	ppm	■ 4	 	
Tin	ppm	6	 	
Aluminum	ppm	6	 	
Chromium	ppm	■1	 	
Molybdenum	ppm	■ 64	 	
Nickel	ppm	■0	 	
Titanium	ppm	■ <1	 	
Silver	ppm	0	 	
Manganese	ppm	2	 	
Vanadium	ppm	<1	 	
ADDITIVES				
Calcium	ppm	2361	 	
Magnesium	ppm	162	 	
Zinc	ppm	■826	 	
Phosphorus	ppm	■952	 	
Barium	ppm	■0	 	
Boron	ppm	■158	 	
	ρρ			

MARINE DIESEL SERVICES INC

1711 WHITTIER AVE, SUITE B
COSTA MESA, CA
US 92627
Contact: BEN ALMAZAN
marinedieselservices@outlook.com
T: (949)612-8180
F: x:

Diagnosis

No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal for OEM. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP288530Unique No:10632164Signed:Doug BogartReport Date:05 Sep 2023

OIL ANALYSIS REPORT



