



WALLENBERG SURVEY ONAN L 150894838 - GENSET

Sample No: VPA057287

Oil Type: DIESEL ENGINE OIL SAE 15W40

| SAMPLE INFORMAT | TION | | | |
|------------------|----------|---------------|------|--|
| Sample Number | | VPA057287 | | |
| Sample Date | | 12 Feb 2024 | | |
| Machine Hours | | 1720 | | |
| Oil Hours | | 0 | | |
| Oil Changed | | Not Changd | | |
| Sample Status | | NORMAL | | |
| OIL CONDITION | | | | |
| Visc @ 100°C | cSt | 13.3 | | |
| Base Number (BN) | mg KOH/g | ■9.7 | | |
| Oxidation (PA) | % | 55 | | |
| CONTAMINATION | | | | |
| | 0/ | NEC | | |
| Water Soot % | % | NEG ■ 0.1 | | |
| Nitration (PA) | % | 42 | | |
| Sulfation (PA) | % | 50 | | |
| Glycol | % | NEG | | |
| Fuel | % | <1.0 | | |
| Silicon | ppm | 11.0 | | |
| Sodium | ppm | ■0 | | |
| Potassium | ppm | ■3 | | |
| WEAR METALS | | | | |
| Iron | nnm | 11 | | |
| Copper | ppm | | | |
| Lead | ppm | ■<1 | | |
| Tin | ppm | 0 | | |
| Aluminum | ppm | 2 | | |
| Chromium | ppm | □ <1 | | |
| Molybdenum | ppm | ■ 57 | | |
| Nickel | ppm | 0 | | |
| Titanium | ppm | ■ 0 | | |
| Silver | ppm | ■ 0 | | |
| Manganese | ppm | ■<1 | | |
| Vanadium | ppm | 0 | | |
| ADDITIVES | | | | |
| Calcium | ppm | 1114 | | |
| Magnesium | ppm | 902 | | |
| Zinc | ppm | 1316 | | |
| Phosphorus | ppm | ■943 | | |
| Barium | ppm | ■0 | | |
| Boron | ppm | 11 | | |
| | | | | |

Suncoast Diesel Marine Inc.

610 Mount Vernan St OLDSMAR, FL US 34677 Contact: MARK WARREN oldsmar@suncoastdmi.com T: (813)475-5942 F: (813)475-5943

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP945077Unique No:10876675Signed:Sean FeltonReport Date:16 Feb 2024

OIL ANALYSIS REPORT



