



STEVE FITHIUM 38 SABRE VOLVO PENTA 3940015538 - PORT IPS

Sample No: VPA054447

Oil Type: GEAR OIL SAE 75W90

| SAMPLE INFORMA | ATION | | | |
|----------------|-------|----------------|------|--|
| 24MFLE INFURM | ATION | | | |
| Sample Number | | VPA054447 | | |
| Sample Date | | 05 Mar 2024 | | |
| Machine Hours | | 775 | | |
| Oil Hours | | 100 | | |
| Oil Changed | | Not Changd | | |
| Sample Status | | NORMAL | | |
| OIL CONDITION | | | | |
| Visc @ 40°C | cSt | □104 | | |
| CONTAMINATION | | | | |
| Water | % | ■ 0.067 | | |
| Silicon | ppm | 4 | | |
| Sodium | ppm | 1 | | |
| Potassium | ppm | 2 | | |
| | le le | | | |
| WEAR METALS | | | | |
| PQ | | 1 5 | | |
| Iron | ppm | 26 | | |
| Copper | ppm | 6 | | |
| Lead | ppm | 0 | | |
| Tin | ppm | <1 | | |
| Aluminum | ppm | 2 | | |
| Chromium | ppm | -< 1 | | |
| Molybdenum | ppm | -<1 | | |
| Nickel | ppm | ■<1 | | |
| Titanium | ppm | <1 | | |
| Silver | ppm | 0 | | |
| Manganese | ppm | | | |
| Vanadium | ppm | 0 | | |
| ADDITIVES | | | | |
| Calcium | ppm | ■83 | | |
| Magnesium | ppm | 2 | | |
| Zinc | ppm | ■27 | | |
| Phosphorus | ppm | ■1267 | | |
| Barium | ppm | ■0 | | |
| Boron | ppm | 289 | | |
| _ 3. 0 | PP.11 | | | |

GRAND BANKS

450 SW SALEM RD STUART, FL US 34994 Contact: ROBERT ANTONA roberta@gbmarinegroup.com T: (609)384-5290 F:

Diagnosis

No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal. The water content is negligible. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP531377Unique No:10914432Signed:Doug BogartReport Date:07 Mar 2024





