



ONAN D180342354 - GENSET

Sample No: VPA053018

Oil Type: DIESEL ENGINE OIL SAE 15W40

SAMPLE INFORMAT	TION			
Sample Number		VPA053018	 	
Sample Date		10 Apr 2024	 	
Machine Hours		746	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		NORMAL	 	
OIL CONDITION				
Visc @ 100°C	cSt	13.44	 	
Base Number (BN)	mg KOH/g	10.0	 	
Oxidation (PA)	%	58	 	
CONTAMINATION				
Water	%	NEG	 	
Soot %	%	■0.1	 	
Nitration (PA)	%	45	 	
Sulfation (PA)	%	52	 	
Glycol	%	NEG	 	
Fuel	%	<1.0	 	
Silicon	ppm	■4	 	
Sodium	ppm	■<1	 	
Potassium	ppm	1	 	
WEAR METALS				
Iron	nnm	<u> </u>	 	
Copper	ppm		 	
Lead	ppm	■ <1	 	
Tin	ppm	0	 	
Aluminum	ppm	= <1	 	
Chromium	ppm	- <1	 	
Molybdenum	ppm	59	 	
Nickel	ppm	■ <1	 	
Titanium	ppm	 <1	 	
Silver	ppm	■0	 	
Manganese	ppm	■<1	 	
Vanadium	ppm	<1	 	
ADDITIVES				
Calcium	nnm	1125	 	
Magnesium	ppm	■ 1123 ■ 1030	 	
Zinc	ppm	■ 1030 ■ 1314	 	
Phosphorus	ppm	■ 1314 ■ 1077	 	
Barium	ppm	■ 1077 ■ <1	 	
Boron	ppm	4	 	
DOTOIT	ppm	4		

SUNCOAST DIESEL MARINE

6341 PORTER ROAD, SUITE 6 SARASOTA, FL US 34240 Contact: SERVICE MANAGER info@suncoastdmi.com T: (941)342-0033

Diagnosis

F:

No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP705283Unique No:10976392Signed:Doug BogartReport Date:11 Apr 2024

OIL ANALYSIS REPORT



