



CARLOS HYDE ONAN B130460699 - GENSET

Sample No: VPA053490

Oil Type: DIESEL ENGINE OIL SAE 15W40

SAMPLE INFORMAT	LIUN			
	HOIN	VDA053400		
Sample Number		VPA053490	 	
Sample Date		21 May 2024	 	
Machine Hours		1990	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
OIL CONDITION				
Visc @ 100°C	cSt	13.4	 	
Base Number (BN)	mg KOH/g	■8.0	 	
Oxidation (PA)	%	69	 	
CONTAMINATION				
Water	%	NEG	 	
Soot %	%	■ 0.1	 	
Nitration (PA)	%	64	 	
Sulfation (PA)	%	53	 	
Glycol	%	NEG	 	
Fuel	%	<1.0	 	
Silicon	ppm	5	 	
Sodium	ppm	4	 	
Potassium	ppm	1	 	
WEAR METALS				
Iron	ppm	7	 	
Copper	ppm	<u>5</u>	 	
Lead	ppm	1	 	
Tin	ppm	□ <1	 	
Aluminum	ppm	1	 	
Chromium	ppm	□ <1	 	
Molybdenum	ppm	1 42	 	
Nickel	ppm	■<1	 	
Titanium	ppm	■ <1	 	
Silver	ppm	□ <1	 	
Manganese	ppm	■ <1	 	
Vanadium	ppm	<1	 	
ADDITIVES				
Calcium	ppm	1452	 	
Magnesium	ррт	1432	 	
Zinc	ppm	1031	 	
Phosphorus	ppm	850	 	
Barium	ppm	■0	 	
Boron	ppm	56	 	
DOTOIT	Phili			

CY MARINE LLC

3821 NW 135th ST, SUITE F OPA LOCKA, FL US 33054 Contact: CAMERON MEDINA cymarinellc@gmail.com T: (954)702-8096 F: x:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Depot:VPCYMPOMUnique No:11044170Signed:Don BaldridgeReport Date:24 May 2024

OIL ANALYSIS REPORT



