



WITACZACK WITACZACK VOLVO PENTA 3200002682 - STARBOARD IPS

Sample No: VPA056688

Oil Type: VOLVO PENTA GL-5 SAE 75W90

| SAMPLE INFORM | ATION | | | |
|-----------------------|-------|--------------|------|--|
| Sample Number | | VPA056688 | | |
| Sample Date | | 24 Jun 2024 | | |
| Machine Hours | | 253 | | |
| Oil Hours | | 200 | | |
| Oil Changed | | Not Changd | | |
| Sample Status | | NORMAL | | |
| | | | | |
| OIL CONDITION | | | | |
| Visc @ 40°C | cSt | 90.6 | | |
| CONTAMINATION | ı | | | |
| Water | % | NEG | | |
| Silicon | ppm | 17 | | |
| Sodium | ppm | 12 | | |
| Potassium | ppm | 11 | | |
| WEAR METALS | | | | |
| | | | | |
| PQ | | ■34 | | |
| Iron | ppm | ■ 106 | | |
| Copper | ppm | 30 | | |
| Lead | ppm | □ <1 | | |
| Tin Aluminum | ppm | ■ <1 | | |
| | ppm | 5 | | |
| Chromium | ppm | ■ <1 | | |
| Molybdenum Nickel | ppm | ■ <1 | | |
| | ppm | 2 | | |
| Titanium | ppm | □ <1 | | |
| Silver | ppm | 0 | | |
| Manganese Vanadium | ppm | 0 | | |
| variauiuffi | ppm | U | | |
| ADDITIVES | | | | |
| Calcium | ppm | ■37 | | |
| Magnesium | ppm | 784 | | |
| Zinc | ppm | 1 5 | | |
| Phosphorus | ppm | 1578 | | |
| Barium | ppm | <u> </u> | | |
| Boron | ppm | ■337 | | |
| | | | | |

Gary Wood's Marine Inc

3469 SW Palm City School Ave #A PALM CITY, FL US 34990 Contact: Barbara Foreman barbara@garywoodsmarine.com T: (772)287-6093 F: (772)287-7134

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VP152567Unique No:11100782Signed:Don BaldridgeReport Date:29 Jun 2024

OIL ANALYSIS REPORT



