

## **OIL ANALYSIS REPORT**

# Hydraulics **INJECTION MOULD #64**

**Hydraulic System** 

{not provided} (--- GAL)

# Sample Rating Trend ISO

#### **DIAGNOSIS**

#### Recommendation

We recommend either performing an oil change or oil filtration. We cannot recommend specific action as we have limited information with regards to reservoir capacity and/or lubricant type.

All component wear rates are normal.

#### Contamination

There is a moderate amount of particulates (5 to 50 microns in size) present in the oil.


#### **Fluid Condition**

The condition of oil is suitable for further service.

				Oct2006		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC22053379		
Sample Date		Client Info		24 Oct 2006		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		7		
Chromium	ppm	ASTM D5185(m)		<1		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		<1		
Aluminum	ppm	ASTM D5185(m)		<1		
Lead	ppm	ASTM D5185(m)		2		
Copper	ppm	ASTM D5185(m)		14		
Tin	ppm	ASTM D5185(m)		2		
Vanadium	ppm	ASTM D5185(m)		0		
ADDITIVES	1-1-	method	limit/base	current	history1	history2
Boron	nnm	ASTM D5185(m)	mm base	<1		
Barium	ppm	ASTM D5185(m)		2		
Molybdenum	ppm	ASTM D5185(m)		<1		
•	ppm	. ,		<1		
Manganese	ppm	ASTM D5185(m)		57		
Magnesium	ppm	ASTM D5185(m)		-		
Calcium	ppm	ASTM D5185(m)		82		
Phosphorus	ppm	ASTM D5185(m)		508		
Zinc	ppm	ASTM D5185(m)		576		
Sulfur	ppm	ASTM D5185(m)		2057		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		9		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)		<1		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		5817		
Particles >6µm		ASTM D7647		<u> </u>		
Particles >14µm		ASTM D7647		<u> </u>		
Particles >21µm		ASTM D7647		75		
Particles >38µm		ASTM D7647		3		
Particles >71µm		ASTM D7647		0		
Oil Cleanliness		ISO 4406 (c)		<u>^</u> 20/18/15		
Oil Cleanliness  FLUID DEGRADA	ATION	ISO 4406 (c)	limit/base	20/18/15 current	history1	history2



### **OIL ANALYSIS REPORT**





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9

: WC22053379 Lab Number : 01338007 Unique Number : 2332392

Received **Tested** Diagnosed : 25 Oct 2006

: 27 Oct 2006

Test Package : IND 2 (Additional Tests: SCREEN) To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

**ABC Manufacturing** 

555 NORTH SERVICE ROAD EAST Detroit. US 76100

Contact: Jim Smith jim.smith@abcmanufacturing.com

> T: (311)555-1212 F: (311)555-1313