


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
Molding
 Machine Id
PRESS 10 (S/N 61002719)
 Component
Hydraulic System
 Fluid
SHELL TELLUS 46 (91 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The system cleanliness is acceptable for your target ISO 4406 cleanliness code.

Fluid Condition

The condition of oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			ST003418	ST004178	---
Sample Date	Client Info			04 Jun 2007	24 Apr 2007	---
Machine Age	hrs	Client Info		0	0	---
Oil Age	hrs	Client Info		0	0	---
Oil Changed	Client Info			N/A	N/A	---
Sample Status				NORMAL	ABNORMAL	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m		2	2	---
Chromium	ppm	ASTM D5185m		<1	<1	---
Nickel	ppm	ASTM D5185m		0	<1	---
Titanium	ppm	ASTM D5185m		0	0	---
Silver	ppm	ASTM D5185m		0	0	---
Aluminum	ppm	ASTM D5185m		0	<1	---
Lead	ppm	ASTM D5185m		0	0	---
Copper	ppm	ASTM D5185m		5	6	---
Tin	ppm	ASTM D5185m		0	0	---
Antimony	ppm	ASTM D5185m		<1	0	---
Vanadium	ppm	ASTM D5185m		0	<1	---
Cadmium	ppm	ASTM D5185m		<1	0	---




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		2	<1	---
Barium	ppm	ASTM D5185m		0	<1	---
Molybdenum	ppm	ASTM D5185m		0	0	---
Manganese	ppm	ASTM D5185m		0	0	---
Magnesium	ppm	ASTM D5185m		<1	1	---
Calcium	ppm	ASTM D5185m		88	94	---
Phosphorus	ppm	ASTM D5185m		289	281	---
Zinc	ppm	ASTM D5185m		294	316	---
Sulfur	ppm	ASTM D5185m		1779	1882	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		<1	<1	---
Sodium	ppm	ASTM D5185m		<1	3	---
Potassium	ppm	ASTM D5185m		0	14	---
Water	%	ASTM D6304		0.006	0.003	---

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		526	▲ 2567	---
Particles >6µm		ASTM D7647		103	▲ 844	---
Particles >14µm		ASTM D7647		8	▲ 125	---
Particles >21µm		ASTM D7647		4	▲ 37	---
Particles >38µm		ASTM D7647		0	6	---
Particles >71µm		ASTM D7647		0	0	---
Oil Cleanliness		ISO 4406 (c)		16/14/10	▲ 19/17/14	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.396	0.479	---

OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	NEG	NEG	---
Free Water	scalar	*Visual	NEG	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	44.49	44.71	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : ST003418 **Received** : 05 Jun 2007
Lab Number : 01970691 **Tested** : 06 Jun 2007
Unique Number : 4124391 **Diagnosed** : 06 Jun 2007 - Doug Bogart
Test Package : IND 2 (Additional Tests: KF)

MENSHEN PACKAGING USA INC.
 21 INDUSTRIAL PARK
 WALDWICK, NJ
 US 07463
 Contact: Jonathan Vanbeekum
 jonathan.vanbeekum@menshen.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)