

OIL ANALYSIS REPORT

FBDL HITACHII ZX245USLC-6 19HI70424

Reference New (Unused) Oil

PANOLIN HLP SYNTH E SPEC (240 LTR)

Sample Rating Trend NORMAL


Recommendation

Il s'agit du relevé de base de l'échantillon soumis.

				Mar2020		
SAMPLE INFORM	/ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		wc		
Sample Date		Client Info		12 Mar 2020		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	V	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		0		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		<1		
Silver	ppm	ASTM D5185(m)		<1		
Aluminum	ppm	ASTM D5185(m)		1		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		0		
Tin	ppm	ASTM D5185(m)		3		
Antimony	ppm	ASTM D5185(m)		<1		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	2		
Barium	ppm	ASTM D5185(m)	0	0		
Molybdenum	ppm	ASTM D5185(m)	0	0		
Manganese	ppm	ASTM D5185(m)	0	0		
Magnesium	ppm	ASTM D5185(m)	0	0		
Calcium	ppm	ASTM D5185(m)	0	1		
Phosphorus	ppm	ASTM D5185(m)	190	193		
Zinc	ppm	ASTM D5185(m)	0	<1		
Sulfur	ppm	ASTM D5185(m)	1750	2014		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		<1		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	<1		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*		0		
Nitration	Abs/cm	ASTM D7624*		2.4		
Sulfation	Abs/.1mm	ASTM D7415*		32.0		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2



OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
/isc @ 40°C	cSt	ASTM D7279(m)	46.5	46.7		
/isc @ 100°C	cSt	ASTM D7279(m)	8.6	8.5		
Viscosity Index (VI)	Scale	ASTM D2270*	165	160		
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						
FT-IR Spectrum (A	bsorban	ce)				
Sample Reference Difference						



CALA ISO 17025:2017 Accredited Laboratory

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Laboratory Sample No. : WC Received Lab Number : 02343933 **Tested** Unique Number : 5019361 Diagnosed

: 20 Mar 2020 - Bill Quesnel Test Package: TEST (Additional Tests: FT-IR, ICP, KV100, KV40, VI)

: 16 Mar 2020

: 20 Mar 2020

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Envirolin Canada 520 rue Adanac Quebec, QC

Contact: Patrick Levesque patrick.levesque@envirolin.com

T: (418)623-1216 F: (418)660-8889

CA G1C 7B7