


FUEL REPORT

GAGAP0504017102

Component **Diesel Fuel**

No.2 DIESEL FUEL (LOW-SULPHUR) (--- GAL)





Recommendation

Laboratory test indicate that this fuel is suitable for use and meets all test requirements. Resample at the next service interval to monitor.

Corrosion

{not applicable}

Contaminants

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. There is no indication of any contamination in the diesel fuel.

Fuel Condition

All laboratory tests indicate that this sample meets specifications for No.2 diesel fuel, low sulfur (US EPA/CGSB-3.517-3 type B).

AL)				Jun2020		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0468215		
Sample Date		Client Info		25 Jun 2020		
Machine Age	hrs	Client Info		0		
Sample Status	1115	Ciletit iiiio		NORMAL		
				NONWAL	1	1
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Specific Gravity		ASTM D1298*	0.839	0.805		
Fuel Color	text	Visual Screen*	Yllow	Pink		
Visc @ 40°C	cSt	ASTM D7279(m)	3.0	1.9		
Pensky-Martens Flash Point	°C	ASTM D7215*	52	55		
SULFUR CONTENT method			limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185(m)	250	84		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D2887*	165	164		
5% Distillation Point	°C	ASTM D2887*		177		
10% Distill Point	°C	ASTM D2887*	201	181		
15% Distillation Point	°C	ASTM D2887*		185		
20% Distill Point	°C	ASTM D2887*	216	190		
30% Distill Point	°C	ASTM D2887*	230	198		
40% Distill Point	°C	ASTM D2887*	243	207		
50% Distill Point	°C	ASTM D2887*	255	217		
60% Distill Point	°C	ASTM D2887*	267	228		
70% Distill Point	°C	ASTM D2887*	280	239		
80% Distill Point	°C	ASTM D2887*	295	254		
85% Distillation Point	°C	ASTM D2887*		268		
90% Distill Point	°C	ASTM D2887*	310	282		
95% Distillation Point	°C	ASTM D2887*		311		
Final Boiling Point	°C	ASTM D2887*	341	353		
IGNITION QUALIT	ГҮ	method	limit/base	current	history1	history2
Cetane Index		ASTM D4737*	<40.0	50		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<1.0	<1		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	<0.1	<1		
Water	%	ASTM D6304*	< 0.05	0.003		
ppm Water	ppm	ASTM D6304*	< 500	25.5		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	1621		
Particles >6µm		ASTM D7647	>640	352		
Particles >14μm		ASTM D7647	>80	35		
Particles >21μm		ASTM D7647	>20	14		
Particles >38µm		ASTM D7647	>4	1		
Particles >71μm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>18/16/13	18/16/12		



FUEL REPORT

