

OIL ANALYSIS REPORT

CARIBOU FALLS GS

Component Governor System Fluid ESSO TERESSO ISO 46 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear


All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0560607	WC0475098	WC944841
Sample Date		Client Info		13 Apr 2021	08 Jul 2020	17 Jul 2018
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	SEVERE
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>50	2	2	1
Chromium	ppm	ASTM D5185(m)		0	0	0
Nickel	ppm	ASTM D5185(m)		0	0	0
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		<1	<1	0
Aluminum	ppm	ASTM D5185(m)	>3	0	<1	0
Lead	ppm	ASTM D5185(m)	>75	<1	0	<1
Copper	ppm	ASTM D5185(m)	>15	<1	<1	0
Tin	ppm	ASTM D5185(m)	>55	0	0	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	<1
ADDITIVES		method	limit/base	current	biotomut	history2
		methou	inniv base	current	history1	TISIOT YZ
Boron	ppm	ASTM D5185(m)	0	<1	0	<1
	ppm ppm					
Boron		ASTM D5185(m)		<1	0	<1
Boron Barium	ppm	ASTM D5185(m) ASTM D5185(m)	0	<1 0	0	<1 0
Boron Barium Molybdenum	ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0	<1 0 0	0 0 0	<1 0 0
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0	<1 0 0 0	0 0 0 0	<1 0 0 0
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0	<1 0 0 0 0	0 0 0 0 0	<1 0 0 0 <1
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 0 2.4	<1 0 0 0 0 <1	0 0 0 0 0 0	<1 0 0 0 <1 <1
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 0 2.4	<1 0 0 0 0 <1 5	0 0 0 0 0 0 3	<1 0 0 <1 <1 4
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 0 2.4	<1 0 0 0 0 <1 5 <1	0 0 0 0 0 0 3 <1	<1 0 0 <1 <1 4 <1
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 0 2.4	<1 0 0 0 <1 5 <1 1286	0 0 0 0 0 0 3 <1 1242	<1 0 0 <1 <1 4 <1 1261
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0	<1 0 0 0 <1 5 <1 1286 <1	0 0 0 0 0 0 3 <1 1242 <1	<1 0 0 <1 <1 4 <1 1261 0
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	0 0 0 0 2.4 0 0	<1 0 0 0 <1 5 <1 1286 <1 1286	0 0 0 0 0 3 <1 1242 <1 1 242 <1 history1	<1 0 0 <1 <1 4 <1 1261 0 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon	ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method ASTM D5185(m)	0 0 0 2.4 0 	<1 0 0 0 <1 5 <1 1286 <1 1286 <1 2 1	0 0 0 0 0 3 <1 1242 <1 history1 <1	<1 0 0 <1 <1 4 <1 1261 0 history2 <1
Boron Barium Molybdenum Manganese Magnesium Calcium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0 !///////////////////////////////////	<1 0 0 0 <1 5 <1 1286 <1 1286 <1 2 1 0	0 0 0 0 0 3 <1 1242 <1 history1 <1 0	<1 0 0 () () () () () () () () () () () () ()
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0 limit/base >8	<1 0 0 0 <1 5 <1 1286 <1 1286 <1 2 1 0 0 0	0 0 0 0 0 3 <1 1242 <1 history1 <1 0 0 0	<1 0 0 <1 <1 4 <1 1261 0 history2 <1 0 0 0
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0 2.4 0 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	<1 0 0 0 <1 5 <1 1286 <1 2 0 current	0 0 0 0 0 3 <1 1242 <1 1242 <1 history1 <1 0 0 0 history1	<1 0 0 () () () () () () () () () () () () ()
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0 2.4 0 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	<1 0 0 0 (1) 5 <1 1286 <1 current (1) 0 0 current 988	0 0 0 0 0 3 <1 1242 <1 history1 <1 0 0 0 history1 1864	<1 0 0 () () () () () () () () () () () () ()
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	0 0 0 2.4 0 2.4 0 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	<1 0 0 0 (1) 5 <1 1286 <1 <u>current</u> <1 0 0 <u>current</u> 988 85	0 0 0 0 0 0 3 <1 1242 <1 history1 <1 0 0 0 history1 1864 157	<1 0 0 0 <1 <1 4 <1 1261 0 history2 <1 0 0 history2 2455 273
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >14µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	0 0 0 2.4 2.4 0 2.4 0 2.4 0 2.4 0 2.4 0 0 0 0 0 0 0 0 0 0 0 0 0	<1 0 0 0 -1 5 <1 1286 <1 <u>current</u> <1 0 0 0 <u>current</u> 988 85 3 1 0 0	0 0 0 0 0 0 3 3 <1 1242 <1 1242 <1 history1 <1 0 0 0 history1 1864 157 2	<1 0 0 0 <1 <1 4 <1 1261 0 history2 <1 0 0 history2 2455 273 12
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >14µm Particles >21µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	0 0 0 2.4 2.4 0 2.4 0 2.4 0 2.4 0 2.4 0 0 0 0 0 0 0 0 0 0 0 0 0	<1 0 0 0 -1 5 <1 1286 <1 <u>current</u> <1 0 0 <u>current</u> 988 85 3 1	0 0 0 0 0 0 3 3 <1 1242 <1 1242 <1 1242 <1 1242 <1 0 0 0 0 history1 1864 157 2 2 2	<1 0 0 () () () () () () () () () () () () ()
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >14µm Particles >21µm Particles >38µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	0 0 0 2.4 2.4 0 2.4 0 2.4 0 2.4 0 2.4 0 0 0 0 0 0 0 0 0 0 0 0 0	<1 0 0 0 -1 5 <1 1286 <1 <u>current</u> <1 0 0 0 <u>current</u> 988 85 3 1 0 0	0 0 0 0 0 3 <1 1242 <1 1242 <1 history1 <1 0 0 0 history1 1864 157 2 2 2 2 0	<1 0 0 0 <1 <1 4 <1 1261 0 history2 <1 0 0 history2 2455 273 12 4 0 0



OIL ANALYSIS REPORT





- 1
5

FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.02	0.05	0.10	0.071
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	47.0	47.0	47.1
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color						

Bottom

MPC



In the second		Laboratory	: WearCheck - C8-	1175 Appleby Lin	e, Burlington, ON L7L 5H9	Ontario Power Generation
		Sample No.	: WC0560607	Received	: 26 May 2021	KENORA PRODUCTION CENTRE, 200-60 FOURTEENTH ST N.
	ISO 17025:2017	Lab Number	: 02423584	Diagnosed	: 27 May 2021	KENORA, ON
Accredited	Unique Number	: 5227084	Diagnostician	: Wes Davis	CA P9N 4M9	
	Laboratory	Test Package	: IND 2 (Additional	Tests: PrtCount,	Contact: Josh Robinson	
	To discuss this sample report, contact Customer Service at 1-800-268-2131.					josh.robinson@opg.com
	Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.					
	Validity of results and interpretation are based on the sample and information as supplied.					