

Area SILVER FALLS

{not provided} (--- LTR)

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

DIAGNOSIS

C1 Component Compressor

Fluid

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. We recommend you service the filters on this component. We recommend an early resample to monitor this condition. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

Particles >4 μ m are abnormally high.

Fluid Condition

Viscosity of sample indicates oil is within ISO 100 range, advise investigate. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC22048580		
Sample Date		Client Info		10 Mar 2022		
Machine Age	mths	Client Info		0		
Oil Age	mths	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water	-	WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>50	8		
Chromium	ppm	ASTM D5185(m)	>10	<1		
Nickel	ppm	ASTM D5185(m)		<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	0		
Lead	ppm	ASTM D5185(m)	>25	0		
Copper	ppm	ASTM D5185(m)	>50	<1		
Tin	ppm	ASTM D5185(m)	>15	0		
Antimony	ppm	ASTM D5185(m)		<1		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		0		
Calcium	ppm	ASTM D5185(m)		<1		
Phosphorus	ppm	ASTM D5185(m)		<1		
Zinc	ppm	ASTM D5185(m)		<1		
Sulfur	ppm	ASTM D5185(m)		2588		
Lithium	ppm	ASTM D5185(m)		0		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	3		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	۰ <1		
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	▲ 59455		
Particles >6µm		ASTM D7647	>2500	1078		
Particles >14µm		ASTM D7647 ASTM D7647	>320	30		
Particles >21µm		ASTM D7647 ASTM D7647		30 7		
i allicies >2 1µ11		ASTM D7647 ASTM D7647	>ou >20	0		
Particles > 29um						
Particles >38µm						
Particles >38µm Particles >71µm Oil Cleanliness		ASTM D7647 ASTM D7647 ISO 4406 (c)	>4 >20/18/15	0 <u>23/17/12</u>		

Page 1 of 2



A Particle

Abnormal 10k 0k Mar10/22

A Particle

Abnormal 10k 0k · Mar10/22

0.03

(B/HO) B/HO) B/HO)

10.01 Piq 0.01 0.00 Mar10/22

100 90 80 cSt (40°C) 70 60.

Abnormal 50.

Abnormal 40-30 Mar10/22

OIL ANALYSIS REPORT

Acid Number (AN)		nethod	limit/base	current	history1	history2
	mg KOH/g AS	5TM D974*		0.02		
VISUAL	r	nethod	limit/base	current	history1	history2
White Metal			NONE	NONE		
Yellow Metal			NONE	NONE		
Precipitate				NONE		
				NONE		
Debris	scalar Vis	sual*	NONE	NONE		
Sand/Dirt	scalar Vis			NONE		
Appearance				NORML		
Odor				NORML		
			>0.1	NEG		
Free Water	scalar Vis	sual*		NEG		
FLUID PROPERT	FIES n	nethod	limit/base	current	history1	history2
Visc @ 40°C	cSt AST	TM D7279(m)		96.4		
	S r	nethod	limit/base	current	history1	history2
Mari						
Color			_		no image	no image
					nonnaye	no image
Bottom				((9))	no image	no image
GRAPHS						
Ferrous Alloys				Particle Count		
iron						T ²⁶
E 5-						+24
			30,720	Abnogmal		-22
0 			27,680	- 1 .		-20
Mar10,			(per 1)			+20 +18 +16
Non-ferrous Meta	ls		sapitus 480			16
NULL-LELLOUS MELA			of ba			1.0
¹⁰ T			5 120			+14
10 copper]			na 120			-14
¹⁰ T			a 120			-14 -12
10 copper]			ag 120 general 30 8			-14
10 copper]			ag 120 general 30 8			-14 -12
Ed 5 CCOper lead			na 120	μ 6μ	14μ 21μ	-14 -12
10 copper]			020 Mar10/22 Mar10/22 Mar10/22	μ 6μ	14μ 21μ	-14 -12
Viscosity @ 40°C			020 Mar10/22 Mar10/22 Mar10/22	μ 6μ	14μ 21μ	-14 -12
Viscosity @ 40°C			020 Mar10/22 Mar10/22 Mar10/22	μ 6μ	14μ 21μ	-14 -12
Viscosity @ 40°C			020 Mar10/22 Mar10/22 Mar10/22	μ 6μ	14μ 21μ	-14 -12
Viscosity @ 40°C			ag 120 general 30 8	μ 6μ	14μ 21μ	-14 -12
	Silt Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPERT Visc @ 40°C SAMPLE IMAGES Color Bottom GRAPHS Ferrous Alloys	Silt scalar Vi Debris scalar Vi Sand/Dirt scalar Vi Appearance scalar Vi Odor scalar Vi Emulsified Water scalar Vi Free Water scalar Vi GRAPHS recommendation of the scalar Vi SAMPLE IMAGES r	Silt scalar Visual* Debris scalar Visual* Sand/Dirt scalar Visual* Appearance scalar Visual* Odor scalar Visual* Emulsified Water scalar Visual* Free Water scalar Visual* Free Water scalar Visual* FLUID PROPERTIES method Visc @ 40°C cSt ASTM D7279(m) SAMPLE IMAGES method Color Bottom GRAPHS Ferrous Alloys Total Scalar Visual*	Silt scalar Visual* NONE Debris scalar Visual* NONE Sand/Dirt scalar Visual* NONE Appearance scalar Visual* NORML Odor scalar Visual* NORML Odor scalar Visual* NORML Odor scalar Visual* NORML Emulsified Water scalar Visual* >0.1 Free Water scalar Visual* >0.1 Free Water scalar Visual* >0.1 Fluid PROPERTIES method limit/base Visc @ 40°C cSt ASTM D7279(m) SAMPLE IMAGES method limit/base Color GRAPHS	Silt scalar Visual* NONE NONE Debris scalar Visual* NONE NONE Sand/Dirt scalar Visual* NONE NONE Appearance scalar Visual* NORML NORML Odor scalar Visual* NORML NORML Emulsified Water scalar Visual* >0.1 NEG Free Water scalar Visual* NEG FLUID PROPERTIES method limit/base current Visc @ 40°C cSt ASTM D7279(m) 96.4 SAMPLE IMAGES method limit/base current Color Bottom GRAPHS Ferrous Alloys Ferrous Alloys Particle Count 122,880 arrent Conter State S	Silt scalar Visual* NONE NONE Debris scalar Visual* NONE NONE Sand/Dirt scalar Visual* NONE NONE Appearance scalar Visual* NORML NORML Codor scalar Visual* NORML NORML Emulsified Water scalar Visual* >0.1 NEG Free Water scalar Visual* NORML NEG Free Water scalar Visual* NEG FLUID PROPERTIES method limit/base current history1 Visc @ 40°C cSt ASTM D7279(m) 96.4 SAMPLE IMAGES method limit/base current history1 Color no image Bottom no image

Report Id: ONT167THU [WCAMIS] 02483626 (Generated: 04/22/2024 14:49:15) Rev: 1

Contact/Location: Bruce Davidson - ONT167THU