

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Machi LOW LIFT #10 MOTOR (S/N FDH284003435) Component Bearing

NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample. Please provide more complete information on your next sample.

Wear

Component wear rates appear to be normal (unconfirmed).

Contamination

There is no indication of any contamination in the component(unconfirmed).

Fluid Condition


The condition of the oil is acceptable for the time in service.


| | Nev2022 | | | | | | | | | | |
|------------------|----------|---------------|------------|-------------|----------|----------|--|--|--|--|--|
| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 | | | | | |
| Sample Number | | Client Info | | WC0757531 | | | | | | | |
| Sample Date | | Client Info | | 03 Nov 2022 | | | | | | | |
| Machine Age | hrs | Client Info | | 0 | | | | | | | |
| Oil Age | hrs | Client Info | | 0 | | | | | | | |
| Oil Changed | | Client Info | | N/A | | | | | | | |
| Sample Status | | | | NORMAL | | | | | | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 | | | | | |
| PQ | | ASTM D8184* | | 0 | | | | | | | |
| Iron | ppm | ASTM D5185(m) | >20 | <1 | | | | | | | |
| Chromium | ppm | ASTM D5185(m) | >20 | 0 | | | | | | | |
| Nickel | ppm | ASTM D5185(m) | >20 | 0 | | | | | | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Silver | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Aluminum | ppm | ASTM D5185(m) | >20 | 0 | | | | | | | |
| Lead | ppm | ASTM D5185(m) | >20 | 9 | | | | | | | |
| Copper | ppm | ASTM D5185(m) | >20 | <1 | | | | | | | |
| Tin | ppm | ASTM D5185(m) | >20 | 0 | | | | | | | |
| Antimony | ppm | ASTM D5185(m) | | <1 | | | | | | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 | | | | | |
| Boron | ppm | ASTM D5185(m) | | <1 | | | | | | | |
| Barium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Molybdenum | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Manganese | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Magnesium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Calcium | ppm | ASTM D5185(m) | | 8 | | | | | | | |
| Phosphorus | ppm | ASTM D5185(m) | | 8 | | | | | | | |
| Zinc | ppm | ASTM D5185(m) | | 8 | | | | | | | |
| Sulfur | ppm | ASTM D5185(m) | | 149 | | | | | | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | | | | | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 | | | | | |
| Silicon | ppm | ASTM D5185(m) | >15 | 3 | | | | | | | |
| Sodium | ppm | ASTM D5185(m) | | 0 | | | | | | | |
| Potassium | ppm | ASTM D5185(m) | >20 | 0 | | | | | | | |
| FLUID DEGRADA | | method | limit/base | current | history1 | history2 | | | | | |
| Acid Number (AN) | mg KOH/g | ASTM D974* | | 0.05 | | | | | | | |



OIL ANALYSIS REPORT







| | VISUAL | | method | | | | history2 |
|--|--|---|-------------------|--|---------------------|-------------------------|----------|
| | White Metal | scalar | Visual* | NONE | NONE | | |
| | Yellow Metal | scalar | Visual* | NONE | NONE | | |
| | Precipitate | scalar | Visual* | NONE | NONE | | |
| - | Silt | scalar | Visual* | NONE | NONE | | |
| | Debris | scalar | Visual* | NONE | NONE | | |
| 2 | Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| Nov3/22 | Appearance | scalar | Visual* | NORML | NORML | | |
| 2 | Odor | scalar | Visual* | NORML | NORML | | |
| | Emulsified Water | scalar | Visual* | >2 | NEG | | |
| | Free Water | scalar | Visual* | | NEG | | |
| | FLUID PROPERT | IES | method | limit/base | current | history1 | history2 |
| | Visc @ 40°C | cSt | ASTM D7279(m) | | 39.8 | | |
| | SAMPLE IMAGES | 3 | method | limit/base | current | history1 | history2 |
| Nov3/22 | Color | | | | | no image | no image |
| | Bottom | | | | | no image | no image |
| | Ferrous Alloys | | | 220 200 180 160 140 200 180 | Severe | | |
| | Non-ferrous Metals | 5 | | | Abnormal | | |
| Ē | 8 - copper | | | | | | |
| ٩ | 4 | | | | | | |
| | | | | 20 | | | |
| | Nov3/22 | | | Nov3/22 | /22 | | |
| | Nov | | | Nov | Nov3/22 | | |
| | Viscosity @ 40°C | | | | Acid Number | | |
| | Abnormal | | | ĵ ^{0.06} | | | |
| 0 | 70 60 Abnormal | | | У В 0 04 | | | |
| × (40° | 60 - Abnormal 50 - | | | per (m | | | |
| 8 | 40- | | | 0.06 0.04 0.04 0.04 0.02 0.00 0.02 | - | | |
| | 30 | | | U.UL | | | |
| | Nov3/22 | | | Nov3/22 | Nov3/22 | | |
| CALA Sample No. 17025:2017 Accredited Laboratory Sample No. Lab Number | : WearCheck - C8-11 : WC0757531 F : 02521443 [| 75 Apple Received Diagnos Diagnosi | d : 08 ed : 08 | | 7L 5H9 ONTAR | ORE RD. W, SOUTH PEEL F | |

ŝ

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Validity of results and interpretation are based on the sample and information as supplied.

T:

F: