

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

NORD TRAVELLING SCREEN 1

Gearbox

Fluid PETRO CANADA PURITY FG EP GEAR OIL 220 (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0761398		
Sample Date		Client Info		08 Nov 2022		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)	>200	2		
Chromium	ppm	ASTM D5185(m)	>15	0		
Nickel	ppm	ASTM D5185(m)	>15	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)	>200	<1		
Tin	ppm	ASTM D5185(m)	>25	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		3		
Barium						
	ppm	ASTM D5185(m)		0		
Molybdenum	ppm ppm	ASTM D5185(m) ASTM D5185(m)		0 0		
Molybdenum Manganese						
	ppm	ASTM D5185(m)		0		
Manganese	ppm ppm	ASTM D5185(m) ASTM D5185(m)		0 0		
Manganese Magnesium	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	135	0 0 0	 	
Manganese Magnesium Calcium	ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	135	0 0 0 0	 	
Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	135	0 0 0 173 3 1851	 	
Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)		0 0 0 173 3	 	
Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)		0 0 0 173 3 1851	 	
Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	660	0 0 0 173 3 1851 1		
Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	660 limit/base	0 0 0 173 3 1851 1	 history1	 history2
Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method ASTM D5185(m)	660 limit/base	0 0 0 173 3 1851 1 current 4	 history1	 history2
Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m)	660 limit/base >50	0 0 0 173 3 1851 1 <i>current</i> 4 <1	 history1	 history2



OIL ANALYSIS REPORT





	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
2	_ Sand/Dirt	scalar	Visual*	NONE	NONE		
Nov8/22	Appearance	scalar	Visual*	NORML	NORML		
~	Oddr	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.2	NEG		
1	Free Water	scalar	Visual*		NEG		
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	225.1	217		
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Nov6/22 -	Color					no image	no image
	Bottom					no image	no image
	GRAPHS	-					
	Ferrous Alloys				PQ		
	10 iron			220			
	chromium			200	Severe		
				180			
	2			160			
	0 L			140	-		
	Nov8/22			ZZ/8^0N 120			
				2 2 100	Abnormal		
	Non-ferrous Metal	S					
	copper			80			
	E 6+			60			
				40			
	2 -						
				22 0			
	Nov8/22			Nov8/22	Nov8/22		
	Viscosity @ 40°C				Acid Number		
	250 Abnormal			(0.60 HO) 0.48 June 10.24 W 0.24 W 0.24 W 0.24 0.00 W 0.02	Base		
				HO 0.48	- 0		
	€ 220			Ĕ 0.36	•		
	³ 210			2 0.24			
	200 Abnormal						
				/8/22	/8/22		
Accredited Unique Number	: <mark>02531788</mark> r : 5512787	Receive Diagnos Diagnos	d : 06 ed : 06 tician : We	lington, ON L Jan 2023 Jan 2023 s Davis		ORE RD. W, SOUTH PEEL F MISS	ACILITIES - LORNE PA ISSAUGA, C CA L5E 1W
Lab Number	: 02531788 r : 5512787 e : IND 2 (Additional T contact Customer Serve	Diagnos Diagnos ests: TAI ice at 1-8	ed : 06 ; tician : We N Man) 300-268-213 :	Jan 2023 s Davis 1.		MISS	ISSAUGA,

Validity of results and interpretation are based on the sample and information as supplied. Report Id: ONT118MIS [WCAMIS] 02531788 (Generated: 10/23/2023 06:44:20) Rev: 1

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

T:

F: